



Size	Profile	LI/SS	TL/TT	3PMSF	Rolling Resistance	Grip	Sound
10R22.5	ADR55	144/142M	TL		D	C	73 dB
12R22.5	ADR55	152/149M	TL		D	C	74 dB
255/70R22.5	ADR55	140/137M(140/140L)	TL		D	B	73 dB
275/70R22.5	ADR55	148/145M	TL		D	C	74 dB

10R22.5

Size	10R22.5
Profile	ADR55
LI/SS	144/142M
Ply rating	16

TL/TT	TL
Application	Long distance
3PMSF	
M+S	Yes
Diameter (mm)	1,025
Width (mm)	258
Rolling circumference (mm)	3,126
Recommended rim	7.50
Tread (mm)	15.5
Load capacity (kg-km/h)	2800.000000
Load capacity (kg-km/h) dual	2650.000000
Air pressure (bar)	9
Wet grip	C 
Fuel efficiency	D 

Sound (decibel)

73 dB ▶

Axle position

Drive axle

12R22.5

Size

12R22.5

Profile

ADR55

LI/SS

152/149M

Ply rating

18

TL/TT

TL

Application

Long distance

3PMSF

M+S




Yes

Diameter (mm)

1,090

Width (mm)

300

Rolling circumference (mm)	3,325
Recommended rim	9.00
Tread (mm)	23
Load capacity (kg-km/h)	3550.000000
Load capacity (kg-km/h) dual	3250.000000
Air pressure (bar)	9.3
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	74 dB 
Axle position	Drive axle

255/70R22.5

Size	255/70R22.5
Profile	ADR55

LI/SS	140/137M(140/140L)
Ply rating	16
TL/TT	TL
Application	Long distance
3PMSF	
M+S	Yes
Diameter (mm)	936
Width (mm)	254
Rolling circumference (mm)	2,855
Recommended rim	7.50
Tread (mm)	20
Load capacity (kg-km/h)	2500.000000
Load capacity (kg-km/h) dual	2300.000000
Air pressure (bar)	8.3

Wet grip

B 

Fuel efficiency

D 

Sound (decibel)

73 dB 

Axle position

Drive axle

275/70R22.5

Size

275/70R22.5

Profile

ADR55

LI/SS

148/145M

Ply rating

18

TL/TT

TL




Application

Long distance

3PMSF

M+S

Yes

Diameter (mm)	975
Width (mm)	274
Rolling circumference (mm)	2,974
Recommended rim	8.25
Tread (mm)	20
Load capacity (kg-km/h)	3150.000000
Load capacity (kg-km/h) dual	2900.000000
Air pressure (bar)	9
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	74 dB 
Axle position	Drive axle