

Size	LI/SS	TL/TT	Air pressure (bar)	
500/45R22.5	148D	TL		Details
500/60R22.5	163D	TL		Details
560/45R22.5	152D	TL		Details
560/60R22.5	165D	TL	4	Details
560/60R22.5	165D	TL	4	Details
560/60R22.5	170D	TL		Details
600/50R22.5	159D	TL	4	Details
600/50R22.5	163D	TL		Details



Size	LI/SS	TL/TT	Air pressure (bar)	
600/55R26.5	177D	TL		Details
600/55R26.5	165D	TL	4	Details
650/55R26.5	169D	TL	4	Details
650/55R26.5	169D	TL	4	Details
650/55R26.5	178D	TL		Details
710/50R26.5	180D	TL		Details
710/50R26.5	170D	TL	4	Details
710/50R30.5	173D	TL		Details
750/60R30.5	190D	TL		Details

Size	LI/SS	TL/TT	Air pressure (bar)
------	-------	-------	--------------------

750/60R30.5

181D

TL

4

Details

500/45R22.5

Size	500/45R22.5
------	-------------

Profile	AE74
---------	------

LI/SS	148D
-------	------

TL/TT	TL
-------	----

Diameter (mm)	1,025
---------------	-------

Width (mm)	505
------------	-----

Recommended rim	AG16.00
-----------------	---------



500/60R22.5

Size	500/60R22.5
Profile	AE74
LI/SS	163D
TL/TT	TL
Diameter (mm)	1,172
Width (mm)	512
Recommended rim	AG16.00

560/45R22.5

Size	560/45R22.5
Profile	AE74

LI/SS	152D
TL/TT	TL
Diameter (mm)	1,076
Width (mm)	549
Recommended rim	AG16.00

560/60R22.5

Size	560/60R22.5
Profile	AE74
LI/SS	165D
TL/TT	TL
Diameter (mm)	1,246
Width (mm)	560
Loaded radius (mm)	548

Rolling circumference (mm)	3,758
-----------------------------------	-------

Recommended rim	16.00
------------------------	-------

560/60R22.5

Size	560/60R22.5
-------------	-------------

Profile	AE74
----------------	------

LI/SS	170D
--------------	------

TL/TT	TL
--------------	----

Diameter (mm)	1,249
----------------------	-------

Width (mm)	560
-------------------	-----

Recommended rim	AG16.00
------------------------	---------

600/50R22.5



Size	600/50R22.5
Profile	AE74
LI/SS	159D
TL/TT	TL
Diameter (mm)	1,181
Width (mm)	614
Loaded radius (mm)	520
Rolling circumference (mm)	3,562
Recommended rim	AG20.00
Load capacity (kg-km/h)	4370.000000

600/50R22.5

Size	600/50R22.5
-------------	-------------

Profile	AE74
LI/SS	163D
TL/TT	TL
Diameter (mm)	1,177
Width (mm)	621
Recommended rim	AG20.00

600/55R26.5

Size	600/55R26.5
Profile	AE74
LI/SS	177D
TL/TT	TL
Diameter (mm)	1,335
Width (mm)	624

Recommended rim	AG20.00
------------------------	---------

600/55R26.5

Size	600/55R26.5
-------------	-------------

Profile	AE74
----------------	------

LI/SS	165D
--------------	------

TL/TT	TL
--------------	----

Diameter (mm)	1,340
----------------------	-------

Width (mm)	618
-------------------	-----

Loaded radius (mm)	590
---------------------------	-----

Rolling circumference (mm)	4,040
-----------------------------------	-------

Recommended rim	AG20.00
------------------------	---------

Load capacity (kg-km/h)	5150.000000
--------------------------------	-------------



650/55R26.5

Size	650/55R26.5
Profile	AE74
LI/SS	169D
TL/TT	TL
Diameter (mm)	1,389
Width (mm)	645
Loaded radius (mm)	612
Rolling circumference (mm)	4,190
Recommended rim	AG20.00
Load capacity (kg-km/h)	5800.000000

650/55R26.5

Size	650/55R26.5
Profile	AE74
LI/SS	169D
TL/TT	TL
Diameter (mm)	1,389
Width (mm)	645
Loaded radius (mm)	612
Rolling circumference (mm)	4,190
Recommended rim	AG20.00
Load capacity (kg-km/h)	5800.000000

650/55R26.5

Size	650/55R26.5
-------------	-------------

Profile	AE74
----------------	------

LI/SS	178D
--------------	------

TL/TT	TL
--------------	----

Diameter (mm)	1,389
----------------------	-------

Width (mm)	645
-------------------	-----

Recommended rim	AG20.00
------------------------	---------

710/50R26.5

Size	710/50R26.5
-------------	-------------

Profile	AE74
----------------	------

LI/SS	180D
--------------	------

TL/TT	TL
--------------	----

Diameter (mm)	1,392
----------------------	-------

Width (mm)	727
-------------------	-----

Recommended rim	AG24.00
------------------------	---------

710/50R26.5

Size	710/50R26.5
-------------	-------------

Profile	AE74
----------------	------

LI/SS	170D
--------------	------

TL/TT	TL
--------------	----

Diameter (mm)	1,392
----------------------	-------

Width (mm)	727
-------------------	-----

Loaded radius (mm)	612
---------------------------	-----

Rolling circumference (mm)	4,198
-----------------------------------	-------

Recommended rim	AG24.00
------------------------	---------

Load capacity (kg-km/h)	6000.000000
--------------------------------	-------------



710/50R30.5

Size	710/50R30.5
Profile	AE74
LI/SS	173D
TL/TT	TL
Diameter (mm)	1,485
Width (mm)	729
Recommended rim	AG24.00

750/60R30.5

Size	750/60R30.5
Profile	AE74

LI/SS	190D
TL/TT	TL
Diameter (mm)	1,670
Šířka (mm)	763
Doporučený ráfek	AG24.00

750/60R30.5

Velikost	750/60R30.5
Profil	AE74
LI/SS	181D
TL/TT	TL
Průměr (mm)	1,675
Šířka (mm)	757
Zatížený poloměr (mm)	738

Obvod válcování (mm)

5,052

Doporučený ráfek

AG24.00

Nosnost (kg-km/h)

8250.000000

|||||

