






















Velikost	Profil	LI/SS	TL/TT	3PMSF	Valivý odpor	Úchop	Zvuk	
215/75R17.5	AGC28	135/133J	TL		E 	C 	73 dB 	Podrobně
235/75R17.5	AGC28	143/141J(144/144F)	TL		E 	B 	74 dB 	Podrobně
245/70R17.5	AGC28	143/141J(144/144F)	TL		E 	B 	74 dB 	Podrobně
265/70R19.5	AGC28	143/141J	TL		E 	B 	74 dB 	Podrobně
255/70R22.5	AGC28	140/137M	TL		E 	B 	74 dB 	Podrobně
275/70R22.5	AGC28	148/145M	TL		D 	B 	74 dB 	Podrobně
385/55R22.5	AGC28	160K(158L)	TL		D 	B 	74 dB 	Podrobně
385/65R22.5	AGC28	160K(158L)	TL					Podrobně

Velikost	Profil	LI/SS	TL/TT	3PMSF	Valivý odpor	Úchop	Zvuk	
385/65R22.5	AGC28	164K(158L)	TL		C ▶	C ▶	74 dB 0 ▶	Podrobně
425/65R22.5	AGC28	165K	TL		C ▶	C ▶	74 dB 0 ▶	Podrobně
445/65R22.5	AGC28	169K	TL		C ▶	C ▶	74 dB 0 ▶	Podrobně

Specifikace




Velikost 215/75R17.5

Profil AGC28

LI/SS 135/133J




Hodnocení vrstvy 18

TL/TT TL

Aplikace	V terénu
3PMSF	
M+S	Ano
Průměr (mm)	766
Šířka (mm)	218
Zatížený poloměr (mm)	356
Rolling circumference (mm)	2,327
Recommended rim	6.00
Tread (mm)	15.5
Air pressure (bar)	8.3
Wet grip	C 
Fuel efficiency	E 
Sound (decibel)	73 dB 
Axle position	All axles




Specifications

Size	235/75R17.5
Profile	AGC28
LI/SS	143/141J(144/144F)
Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	804
Width (mm)	236
Loaded radius (mm)	368
Rolling circumference (mm)	2,440

Recommended rim	6.75
Tread (mm)	16.5
Air pressure (bar)	9
Wet grip	B 
Fuel efficiency	E 
Sound (decibel)	74 dB 
Axle position	All axles




Specifications

Size	245/70R17.5
Profile	AGC28
LI/SS	143/141J(144/144F)
Ply rating	18
TL/TT	TL

Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	793
Width (mm)	252
Loaded radius (mm)	364
Rolling circumference (mm)	2,418
Recommended rim	7.50
Tread (mm)	16.5
Air pressure (bar)	9
Wet grip	B 
Fuel efficiency	E 
Sound (decibel)	74 dB 
Axle position	All axles




Specifications

Size	265/70R19.5
Profile	AGC28
LI/SS	143/141J
Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	877
Width (mm)	258
Loaded radius (mm)	407
Rolling circumference (mm)	2,674

Recommended rim	7.50
Tread (mm)	17.5
Air pressure (bar)	8.3
Wet grip	B 
Fuel efficiency	E 
Sound (decibel)	74 dB 
Axle position	All axles

Specifications

Size	255/70R22.5
Profile	AGC28
LI/SS	140/137M
Ply rating	16
TL/TT	TL

Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	932
Width (mm)	254
Rolling circumference (mm)	2,842
Recommended rim	7.50
Tread (mm)	17.5
Load capacity (kg-km/h)	2500.000000
Load capacity (kg-km/h) dual	2300.000000
Air pressure (bar)	8.3
Wet grip	B 
Fuel efficiency	E 
Sound (decibel)	74 dB 

Axle position

All axles

Specifications

Size

275/70R22.5

Profile

AGC28

LI/SS

148/145M

Ply rating

18

TL/TT

TL

Application

On-offroad

3PMSF

M+S

Yes

Diameter (mm)




968

Width (mm)

272


Loaded radius (mm)

450

Rolling circumference (mm)	2,952
Recommended rim	8.25
Tread (mm)	17.5
Air pressure (bar)	9
Wet grip	B 
Fuel efficiency	D 
Sound (decibel)	74 dB 
Axle position	All axles

Specifications

Size	385/55R22.5
Profile	AGC28
LI/SS	160K(158L)
Ply rating	20

TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,004
Width (mm)	386
Loaded radius (mm)	463
Rolling circumference (mm)	3,151
Recommended rim	11.75
Tread (mm)	17
Load capacity (kg-km/h)	4500.000000
Load capacity (kg-km/h) dual	4250.000000
Air pressure (bar)	9
Wet grip	B 

Fuel efficiency

D 

Sound (decibel)

74 dB 

Axle position

All axles

Specifications

Size

385/65R22.5

Profile

AGC28

LI/SS

160K(158L)

Ply rating

20

TL/TT

TL

Application

On-offroad

3PMSF

M+S

Yes

Diameter (mm)

1,070

Width (mm)	387
Loaded radius (mm)	495
Rolling circumference (mm)	3,264
Recommended rim	11.75
Tread (mm)	16.8
Load capacity (kg-km/h)	5000.000000
Load capacity (kg-km/h) dual	4250.000000
Air pressure (bar)	9
Axle position	All axles

Specifications

Size	385/65R22.5
Profile	AGC28
LI/SS	164K(158L)

Ply rating	20
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,070
Width (mm)	387
Loaded radius (mm)	495
Rolling circumference (mm)	3,264
Recommended rim	11.75
Tread (mm)	16.8
Load capacity (kg-km/h)	5000.000000
Load capacity (kg-km/h) dual	4250.000000
Air pressure (bar)	9

Wet grip

C 

Fuel efficiency

C 

Sound (decibel)

74 dB 

Axle position

All axles

Specifications

Size

425/65R22.5

Profile

AGC28

LI/SS

165K

Ply rating

20

TL/TT

TL




Application

On-offroad

3PMSF

M+S

Yes

Diameter (mm)	1,118
Width (mm)	422
Loaded radius (mm)	519
Rolling circumference (mm)	3,387
Recommended rim	12.25
Tread (mm)	16.5
Air pressure (bar)	8.3
Wet grip	C 
Fuel efficiency	C 
Sound (decibel)	74 dB 
Axle position	All axles

Specifications

Size 445/65R22.5

Profile	AGC28
LI/SS	169K
Ply rating	20
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,147
Width (mm)	453
Loaded radius (mm)	525
Rolling circumference (mm)	3,602
Recommended rim	13.00
Tread (mm)	16.5
Air pressure (bar)	8.3


Wet grip

C 

Fuel efficiency

C 

Sound (decibel)

74 dB 

Axle position

All axles
