

Size	Profile	LI/SS	TL/TT	3PMSF	Rolling Resistance	Grip	Sound	
245/70R19.5	ASR79	144/142J	TL		E	C	72 dB	D€
265/70R19.5	ASR79	143/141J	TL		D	C	71 dB (1)	D€
11R22.5	ASR79	146/143M(148/145L)	TL		D	C	71 dB	D€
255/70R22.5	ASR79	140/137M(140/140L)	TL		D	C	72 dB	D€
295/60R22.5	ASR79	150/147K(149/146L)	TL		D	C	73 dB	D€

Specifications

Size

245/70R19.5

Profile

ASR79

LI/SS	144/142J
Ply rating	18
TL/TT	TL
Application	Regional transport
3PMSF	
M+S	Yes
Diameter (mm)	853
Width (mm)	248
Rolling circumference (mm)	2,602
Recommended rim	7.50
Tread (mm)	15
Load capacity (kg-km/h)	2800.000000
Load capacity (kg-km/h) dual	2650.000000
Air pressure (bar)	9


Wet grip

C 

Fuel efficiency

E 

Sound (decibel)

72 dB 

Axle position

Steer axle

Specifications

Size

265/70R19.5

Profile

ASR79

LI/SS

143/141J

Ply rating

18

TL/TT

TL




Application

Regional transport

3PMSF


M+S

Yes

Diameter (mm)	867
Width (mm)	258
Rolling circumference (mm)	2,644
Recommended rim	7.50
Tread (mm)	13
Load capacity (kg-km/h)	2720.000000
Load capacity (kg-km/h) dual	2570.000000
Air pressure (bar)	8.3
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	71 dB 
Sound (wave)	1
Axle position	Steer axle



Specifications

Size	11R22.5
Profile	ASR79
LI/SS	146/143M(148/145L)
Ply rating	16
TL/TT	TL
Application	Regional transport
3PMSF	
M+S	Yes
Diameter (mm)	1,051
Width (mm)	280
Rolling circumference (mm)	3,206
Recommended rim	8.25

Tread (mm)	15
Load capacity (kg-km/h)	3000.000000
Load capacity (kg-km/h) dual	2725.000000
Air pressure (bar)	8.3
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	71 dB 
Axle position	Steer axle

Specifications

Size	255/70R22.5
Profile	ASR79
LI/SS	140/137M(140/140L)
Ply rating	16

TL/TT	TL
Application	Regional transport
3PMSF	
M+S	Yes
Diameter (mm)	928
Width (mm)	250
Rolling circumference (mm)	2,830
Recommended rim	7.50
Tread (mm)	15
Load capacity (kg-km/h)	2500.000000
Load capacity (kg-km/h) dual	2300.000000
Air pressure (bar)	8.3
Wet grip	C 
Fuel efficiency	D 

Sound (decibel)

72 dB ▶

Axle position

Steer axle

Specifications

Size

295/60R22.5

Profile

ASR79

LI/SS

150/147K(149/146L)

Ply rating

18

TL/TT

TL

Application

Regional transport

3PMSF

M+S




Yes

Diameter (mm)

919

Width (mm)

292

Rolling circumference (mm)	2,802
Recommended rim	9.00
Tread (mm)	15
Load capacity (kg-km/h)	3350.000000
Load capacity (kg-km/h) dual	3075.000000
Air pressure (bar)	9
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	73 dB 
Axle position	Steer axle
