

| Velikost | Profil | LI/SS | TL/TT | 3PMSF | Valivý odpor | Úchop | Zvuk | |
|-------------|----------------------|----------|-------|-------|--------------|----------|-----------|--------------------------|
| 205/75R17.5 | NEO ALLROADS S | 124/122M | TL | | | | | Podrobně |
| 215/75R17.5 | NEO ALLROADS S | 126/124M | TL | | D | B | 69 dB | Podrobně |
| 215/75R17.5 | NEO ALLROADS S | 126/124M | TL | | D | C | 72 dB | Podrobně |
| 235/75R17.5 | NEO ALLROADS S | 132/130M | TL | | D | C | 72 dB | Podrobně |
| 235/75R17.5 | NEO ALLROADS S | 132/130M | TL | | D | C | 73 dB (2) | Podrobně |

| Velikost | Profil | LI/SS | TL/TT | 3PMSF | Valivý odpor | Úchop | Zvuk | |
|-------------|----------------------|--------------------|-------|-------|--------------|-------|-------|--------------------------|
| 245/70R17.5 | NEO ALLROADS S | 136/134M | TL | | D | C | 72 dB | Podrobně |
| 265/70R19.5 | NEO ALLROADS S | 140M | TL | | C | B | 72 dB | Podrobně |
| 285/70R19.5 | NEO ALLROADS S | 145/143M(146/144L) | TL | | C | C | 72 dB | Podrobně |
| 275/70R22.5 | NEO ALLROADS S | 148/145M | TL | | D | B | 72 dB | Podrobně |
| 295/80R22.5 | NEO ALLROADS S | 154/149M | TL | | C | B | 70 dB | Podrobně |

| Velikost | Profil | LI/SS | TL/TT | 3PMSF | Valivý odpor | Úchop | Zvuk | |
|-------------|----------------------|--------------------|-------|-------|--------------|-------|-------|--------------------------|
| 295/80R22.5 | NEO ALLROADS S | 154/149M | TL | | D | C | 72 dB | Podrobně |
| 315/70R22.5 | NEO ALLROADS S | 156/150L(152/148M) | TL | | B | B | 73 dB | Podrobně |
| 315/70R22.5 | NEO ALLROADS S | 156/150L(154/150M) | TL | | C | B | 69 dB | Podrobně |
| 315/80R22.5 | NEO ALLROADS S | 158/150L(154/150M) | TL | | C | B | 71 dB | Podrobně |
| 315/80R22.5 | NEO ALLROADS S | 158/150L(154/150M) | TL | | B | C | 73 dB | Podrobně |

205/75R17.5

| | |
|---------------------------------|--------------------|
| Velikost | 205/75R17.5 |
| Profil | NEO ALLROADS S |
| LI/SS | 124/122M |
| Hodnocení vrstvy | 14 |
| TL/TT | TL |
| Aplikace | Regionální doprava |
| 3PMSF | |
| M+S | Ne |
| Doporučený ráfek | 6.00 |
| Běhoun (mm) | 12.5 |
| Nosnost (kg-km/h) | 1600,000000 |
| Nosnost (kg-km/h) duální | 1500,000000 |

Tlak vzduchu (bar)

7.6

Poloha nápravy

Řízená náprava

215/75R17.5

Velikost

215/75R17.5

Profil

NEO ALLROADS S

LI/SS

126/124M

Hodnocení vrstvy

16

TL/TT

TL

Aplikace

Regionální doprava

3PMSF

M+S

Ano

Průměr (mm)

761


Šířka (mm)

218

| | |
|---------------------------------|---|
| Obvod válcování (mm) | 2,321 |
| Doporučený ráfek | 6.00 |
| Běhoun (mm) | 12.5 |
| Nosnost (kg-km/h) | 1700,000000 |
| Nosnost (kg-km/h) duální | 1600,000000 |
| Tlak vzduchu (bar) | 7 |
| Vlhký úchop | B  |
| Palivová účinnost | D  |
| Zvuk (decibel) | 69 dB  |
| Poloha nápravy | Řízená náprava |

215/75R17.5

| | |
|-----------------|----------------|
| Velikost | 215/75R17.5 |
| Profil | NEO ALLROADS S |

| | |
|---------------------------------|---|
| LI/SS | 126/124M |
| Hodnocení vrstvy | 16 |
| TL/TT | TL |
| Aplikace | Regionální doprava |
| 3PMSF | |
| M+S | Ano |
| Průměr (mm) | 761 |
| Šířka (mm) | 218 |
| Obvod válcování (mm) | 2,321 |
| Doporučený ráfek | 6.00 |
| Běhoun (mm) | 12.5 |
| Nosnost (kg-km/h) | 1700,000000 |
| Nosnost (kg-km/h) duální | 1600,000000 |
| Tlak vzduchu (bar) | 7 |
| Vlhký úchop | C  |

Palivová účinnost

D 

Zvuk (decibel)

72 dB 

Poloha nápravy

Řízená náprava

235/75R17.5

Velikost

235/75R17.5

Profil

NEO ALLROADS S

LI/SS

132/130M

Hodnocení vrstvy

16

TL/TT

TL

Aplikace

Regionální doprava


3PMSF

M+S

Ano

Průměr (mm)

793

| | |
|------------------------------|---|
| Šířka (mm) | 235 |
| Zatížený poloměr (mm) | 370 |
| Obvod válcování (mm) | 2,419 |
| Doporučený ráfek | 6.75 |
| Tread (mm) | 13 |
| Load capacity (kg-km/h) | 2000.000000 |
| Load capacity (kg-km/h) dual | 1900.000000 |
| Air pressure (bar) | 8.3 |
| Wet grip | C  |
| Fuel efficiency | D  |
| Sound (decibel) | 72 dB  |
| Axle position | Steer axle |

235/75R17.5

| | |
|-----------------------------------|--------------------|
| Size | 235/75R17.5 |
| Profile | NEO ALLROADS S |
| LI/SS | 132/130M |
| Ply rating | 16 |
| TL/TT | TL |
| Application | Regional transport |
| M+S | Yes |
| Diameter (mm) | 793 |
| Width (mm) | 235 |
| Loaded radius (mm) | 370 |
| Rolling circumference (mm) | 2,419 |
| Recommended rim | 6.75 |
| Tread (mm) | 13 |
| Air pressure (bar) | 8.3 |


Wet grip

C 

Fuel efficiency

D 

Sound (decibel)

73 dB 

Sound (wave)

2

Axle position

Steer axle

245/70R17.5

Size

245/70R17.5

Profile

NEO ALLROADS S

LI/SS

136/134M

Ply rating

18

TL/TT

TL

Application

Regional transport



3PMSF

| | |
|-----------------------------------|--|
| M+S | Yes |
| Diameter (mm) | 792 |
| Width (mm) | 250 |
| Rolling circumference (mm) | 2,416 |
| Recommended rim | 7.50 |
| Tread (mm) | 15 |
| Air pressure (bar) | 8.5 |
| Wet grip | C  |
| Fuel efficiency | D  |
| Sound (decibel) | 72 dB  |
| Axle position | Steer axle |


265/70R19.5

Size

265/70R19.5

| | |
|-----------------------------------|---|
| Profile | NEO ALLROADS S |
| LI/SS | 140M |
| TL/TT | TL |
| Application | Regional transport |
| 3PMSF | |
| M+S | Yes |
| Diameter (mm) | 868 |
| Width (mm) | 260 |
| Rolling circumference (mm) | 2,647 |
| Recommended rim | 7.50 |
| Tread (mm) | 13 |
| Load capacity (kg-km/h) | 2500.000000 |
| Air pressure (bar) | 8.5 |
| Wet grip | B  |
| Fuel efficiency | C  |

Sound (decibel)

72 dB 

Axle position

Steer axle

285/70R19.5

Size

285/70R19.5

Profile

NEO ALLROADS S

LI/SS

145/143M(146/144L)

Ply rating

18

TL/TT

TL

Application

Regional transport

3PMSF

M+S




Yes

Diameter (mm)

892



Width (mm)

291


| | |
|-------------------------------------|---|
| Rolling circumference (mm) | 2,721 |
| Recommended rim | 8.25 |
| Tread (mm) | 14 |
| Load capacity (kg-km/h) | 2900.000000 |
| Load capacity (kg-km/h) dual | 2720.000000 |
| Air pressure (bar) | 8.5 |
| Wet grip | C  |
| Fuel efficiency | C  |
| Sound (decibel) | 72 dB  |
| Axle position | Steer axle |

275/70R22.5

| | |
|----------------|----------------|
| Size | 275/70R22.5 |
| Profile | NEO ALLROADS S |

| | |
|-------------------------------------|---|
| LI/SS | 148/145M |
| TL/TT | TL |
| Application | Regional transport |
| 3PMSF | |
| M+S | No |
| Diameter (mm) | 963 |
| Width (mm) | 281 |
| Rolling circumference (mm) | 2,955 |
| Recommended rim | 8.25 |
| Tread (mm) | 16.5 |
| Load capacity (kg-km/h) | 3150.000000 |
| Load capacity (kg-km/h) dual | 2900.000000 |
| Air pressure (bar) | 9 |
| Wet grip | B  |
| Fuel efficiency | D  |

Sound (decibel)

72 dB 

Axle position

Steer axle

295/80R22.5

Size

295/80R22.5

Profile

NEO ALLROADS S

LI/SS

154/149M

Ply rating

18

TL/TT

TL

Application

Regional transport

3PMSF

M+S




Yes

Diameter (mm)

1,080

Width (mm)

298

| | |
|-------------------------------------|---|
| Rolling circumference (mm) | 3,294 |
| Recommended rim | 9.00 |
| Tread (mm) | 16.5 |
| Load capacity (kg-km/h) | 3750.000000 |
| Load capacity (kg-km/h) dual | 3250.000000 |
| Air pressure (bar) | 9 |
| Wet grip | B  |
| Fuel efficiency | C  |
| Sound (decibel) | 70 dB  |
| Axle position | Steer axle |

295/80R22.5

| | |
|----------------|----------------|
| Size | 295/80R22.5 |
| Profile | NEO ALLROADS S |

| | |
|-------------------------------------|--------------------|
| LI/SS | 154/149M |
| Ply rating | 18 |
| TL/TT | TL |
| Application | Regional transport |
| 3PMSF | |
| M+S | Yes |
| Diameter (mm) | 1,080 |
| Width (mm) | 298 |
| Loaded radius (mm) | 490 |
| Rolling circumference (mm) | 3,294 |
| Recommended rim | 9.00 |
| Tread (mm) | 16.5 |
| Load capacity (kg-km/h) | 3750.000000 |
| Load capacity (kg-km/h) dual | 3250.000000 |
| Air pressure (bar) | 9 |


Wet grip

C 

Fuel efficiency

D 

Sound (decibel)

72 dB 

Axle position

Steer axle

315/70R22.5

Size

315/70R22.5

Profile

NEO ALLROADS S

LI/SS

156/150L(152/148M)

Ply rating

18

TL/TT

TL




Application

Regional transport

3PMSF

M+S

Yes

| | |
|-------------------------------------|--|
| Diameter (mm) | 1,020 |
| Width (mm) | 310 |
| Loaded radius (mm) | 469 |
| Recommended rim | 9.00 |
| Tread (mm) | 15.5 |
| Load capacity (kg-km/h) | 4000.000000 |
| Load capacity (kg-km/h) dual | 3350.000000 |
| Wet grip | B  |
| Fuel efficiency | B  |
| Sound (decibel) | 73 dB  |
| Axle position | Steer axle |

315/70R22.5

Size 315/70R22.5

| | |
|-------------------------------------|--------------------|
| Profile | NEO ALLROADS S |
| LI/SS | 156/150L(154/150M) |
| Ply rating | 18 |
| TL/TT | TL |
| Application | Regional transport |
| 3PMSF | |
| M+S | Yes |
| Diameter (mm) | 1,020 |
| Width (mm) | 310 |
| Rolling circumference (mm) | 3,102 |
| Recommended rim | 9.00 |
| Tread (mm) | 15.5 |
| Load capacity (kg-km/h) | 4000.000000 |
| Load capacity (kg-km/h) dual | 3350.000000 |
| Air pressure (bar) | 8 |

Wet grip

B 

Fuel efficiency

C 

Sound (decibel)

69 dB 

Axle position

Steer axle

315/80R22.5

Size

315/80R22.5

Profile

NEO ALLROADS S

LI/SS

158/150L(154/150M)

Ply rating

18

TL/TT

TL




Application

Regional transport

3PMSF




M+S

Yes

| | |
|-------------------------------------|---|
| Diameter (mm) | 1,085 |
| Width (mm) | 316 |
| Loaded radius (mm) | 500 |
| Rolling circumference (mm) | 3,309 |
| Recommended rim | 9.00 |
| Tread (mm) | 16 |
| Load capacity (kg-km/h) | 4250.000000 |
| Load capacity (kg-km/h) dual | 3350.000000 |
| Air pressure (bar) | 9 |
| Wet grip | B  |
| Fuel efficiency | C  |
| Sound (decibel) | 71 dB  |
| Axle position | Steer axle |

315/80R22.5

| | |
|-----------------------------------|--------------------|
| Size | 315/80R22.5 |
| Profile | NEO ALLROADS S |
| LI/SS | 158/150L(154/150M) |
| Ply rating | 18 |
| TL/TT | TL |
| Application | Regional transport |
| 3PMSF | |
| M+S | Yes |
| Diameter (mm) | 1,085 |
| Width (mm) | 316 |
| Loaded radius (mm) | 500 |
| Rolling circumference (mm) | 3,309 |

| | |
|-------------------------------------|---|
| Recommended rim | 9.00 |
| Tread (mm) | 16 |
| Load capacity (kg-km/h) | 4250.000000 |
| Load capacity (kg-km/h) dual | 3350.000000 |
| Air pressure (bar) | 9 |
| Wet grip | C  |
| Fuel efficiency | B  |
| Sound (decibel) | 73 dB  |
| Axle position | Steer axle |