
















Velikost	Profil	LI/SS	TL/TT	3PMSF	Valivý odpor	Úchop	Zvuk	
13R22.5	NEO CONSTRUCT D	156/150K	TL		D 	A 	76 dB 	Podrobn
13R22.5	NEO CONSTRUCT D	156/150K	TL		D 	C 	74 dB 	Podrobn
315/80R22.5	NEO CONSTRUCT D	156/150K(154/150M)	TL		D 	C 	75 dB 	Podrobn
315/80R22.5	NEO CONSTRUCT D	156/150K(154/150M)	TL		D 	B 	76 dB 	Podrobn
325/95R24	NEO CONSTRUCT D	162/160K	TL		C 	C 	74 dB 	Podrobn


13R22.5

Velikost	13R22.5
Profil	NEO CONSTRUCT D
LI/SS	156/150K
Hodnocení vrstvy	18
TL/TT	TL
Aplikace	V terénu
3PMSF	
M+S	Ano
Průměr (mm)	1,130
Šířka (mm)	306
Zatížený poloměr (mm)	521
Obvod válcování (mm)	3,447

Doporučený ráfek	9.00
Běhoun (mm)	22
Nosnost (kg-km/h)	4000,000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.75
Wet grip	A 
Fuel efficiency	D 
Sound (decibel)	76 dB 
Axle position	Drive axle

13R22.5

Size	13R22.5
Profile	NEO CONSTRUCT D
LI/SS	156/150K

Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,130
Width (mm)	306
Loaded radius (mm)	521
Rolling circumference (mm)	3,447
Recommended rim	9.00
Tread (mm)	22
Load capacity (kg-km/h)	4000.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.75
Wet grip	c 

Fuel efficiency

D 

Sound (decibel)

74 dB 

Axle position

Drive axle

315/80R22.5

Size

315/80R22.5

Profile

NEO CONSTRUCT D

LI/SS

156/150K(154/150M)

Ply rating

18

TL/TT

TL

Application

On-offroad



3PMSF

M+S

Yes




Diameter (mm)

1,095

Width (mm)	315
Loaded radius (mm)	500
Rolling circumference (mm)	3,340
Recommended rim	9.00
Tread (mm)	23
Load capacity (kg-km/h)	4000.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.5
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	75 dB 
Axle position	Drive axle

315/80R22.5

Size	315/80R22.5
Profile	NEO CONSTRUCT D
LI/SS	156/150K(154/150M)
Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,095
Width (mm)	315
Loaded radius (mm)	500
Rolling circumference (mm)	3,340
Recommended rim	9.00
Tread (mm)	23

Load capacity (kg-km/h)	4000.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.5
Wet grip	B 
Fuel efficiency	D 
Sound (decibel)	76 dB 
Axle position	Drive axle

325/95R24

Size	325/95R24
Profile	NEO CONSTRUCT D
LI/SS	162/160K
Ply rating	22
TL/TT	TL

Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,230
Width (mm)	314
Rolling circumference (mm)	3,752
Recommended rim	8.50
Tread (mm)	20.6
Air pressure (bar)	8.5
Wet grip	C 
Fuel efficiency	C 
Sound (decibel)	74 dB 
Axle position	Drive axle