




Size	Profile	LI/SS	TL/TT	3PMSF	Rolling Resistance	Grip	Sound	
13R22.5	NEO CONSTRUCT G	156/150K(154/150M)	TL		D	C	73 dB	De
13R22.5	NEO CONSTRUCT G	156/150K(154/150M)	TL		D	B	71 dB	De
315/80R22.5	NEO CONSTRUCT G	158/150K	TL		C	B	73 dB	De
315/80R22.5	NEO CONSTRUCT G	158/150K	TL		D	B	71 dB	De
425/65R22.5	NEO CONSTRUCT G	165K	TL		C	C	74 dB	De

Size	Profile	LI/SS	TL/TT	3PMSF	Rolling Resistance	Grip	Sound
325/95R24	NEO CONSTRUCT G	162/160K	TL		C ▶	C ▶	73 dB () ▶ De




13R22.5

Size	13R22.5
Profile	NEO CONSTRUCT G
LI/SS	156/150K(154/150M)
Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes

Diameter (mm)	1,125
Width (mm)	318
Loaded radius (mm)	521
Rolling circumference (mm)	3,431
Recommended rim	9.00
Tread (mm)	18
Load capacity (kg-km/h)	4000.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.75
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	73 dB 
Axle position	All axles


13R22.5

Size	13R22.5
Profile	NEO CONSTRUCT G
LI/SS	156/150K(154/150M)
Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,125
Width (mm)	318
Loaded radius (mm)	521
Rolling circumference (mm)	3,431

Recommended rim	9.00
Tread (mm)	18
Load capacity (kg-km/h)	4000.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	8.75
Wet grip	B 
Fuel efficiency	D 
Sound (decibel)	71 dB 
Axle position	All axles

315/80R22.5

Size	315/80R22.5
Profile	NEO CONSTRUCT G
LI/SS	158/150K

Ply rating	18
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,084
Width (mm)	317
Loaded radius (mm)	500
Rolling circumference (mm)	3,306
Recommended rim	9.00
Tread (mm)	16.5
Load capacity (kg-km/h)	4250.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	9
Wet grip	B 

Fuel efficiency

C 

Sound (decibel)

73 dB 

Axle position

All axles

315/80R22.5

Size

315/80R22.5

Profile

NEO CONSTRUCT G

LI/SS

158/150K

Ply rating

18

TL/TT

TL

Application

On-offroad

3PMSF

M+S

Yes

Diameter (mm)

1,084

Width (mm)	317
Loaded radius (mm)	500
Rolling circumference (mm)	3,306
Recommended rim	9.00
Tread (mm)	16.5
Load capacity (kg-km/h)	4250.000000
Load capacity (kg-km/h) dual	3350.000000
Air pressure (bar)	9
Wet grip	B 
Fuel efficiency	D 
Sound (decibel)	71 dB 
Axle position	All axles

425/65R22.5

Size	425/65R22.5
Profile	NEO CONSTRUCT G
LI/SS	165K
Ply rating	20
TL/TT	TL
Application	On-offroad
3PMSF	
M+S	Yes
Diameter (mm)	1,125
Width (mm)	419
Rolling circumference (mm)	3,431
Recommended rim	12.25
Tread (mm)	19
Load capacity (kg-km/h)	5150.000000

Air pressure (bar)

8.25

Wet grip

C 

Fuel efficiency

C 

Sound (decibel)

74 dB 

Axle position

All axles

325/95R24

Size

325/95R24

Profile

NEO CONSTRUCT G

LI/SS

162/160K

Ply rating

22




TL/TT

TL

Application

On-offroad

3PMSF

M+S	Yes
Diameter (mm)	1,231
Width (mm)	322
Rolling circumference (mm)	3,755
Recommended rim	8.5
Tread (mm)	19
Load capacity (kg-km/h)	4750.000000
Load capacity (kg-km/h) dual	4500.000000
Air pressure (bar)	8.5
Wet grip	C 
Fuel efficiency	C 
Sound (decibel)	73 dB 
Axle position	All axles