

Velikost	Profil	LI/SS	TL/TT	3PMSF	Valivý odpor	Úchop	Zvuk	
275/70R22.5	NEO URBAN G	150/148J(152/148E)	TL		C	B	73 dB	Podrobnosti
295/80R22.5	NEO URBAN G	154/149M	TL		B	B	72 dB	Podrobnosti
305/70R22.5	NEO URBAN G	152/150L	TL		D	C	72 dB	Podrobnosti

275/70R22.5

Velikost

275/70R22.5

Profil

NEO URBAN G

LI/SS

150/148J(152/148E)

Hodnocení vrstvy	18
TL/TT	TL
Aplikace	Město
3PMSF	
M+S	Ano
Průměr (mm)	966
Šířka (mm)	272
Zatížený poloměr (mm)	449
Obvod válcování (mm)	2,946
Doporučený ráfek	8.25
Běhoun (mm)	18
Tlak vzduchu (bar)	9
Vlhký úchop	B 
Palivová účinnost	C 
Zvuk (decibel)	73 dB 

Poloha nápravy

Všechny nápravy

295/80R22.5

Size 295/80R22.5

Profile NEO URBAN G

LI/SS 154/149M

Ply rating 18

TL/TT TL

Application City

3PMSF

M+S Yes

Diameter (mm) 1,061




Width (mm) 308

Loaded radius (mm) 495

Rolling circumference (mm)	3,236
Recommended rim	9.00
Tread (mm)	18
Air pressure (bar)	9
Wet grip	B 
Fuel efficiency	B 
Sound (decibel)	72 dB 
Axle position	All axles

305/70R22.5

Size	305/70R22.5
Profile	NEO URBAN G
LI/SS	152/150L
Ply rating	20

TL/TT	TL
Application	City
3PMSF	
M+S	Yes
Diameter (mm)	1,000
Width (mm)	300
Loaded radius (mm)	452
Rolling circumference (mm)	3,050
Recommended rim	9.00
Tread (mm)	19
Air pressure (bar)	9
Wet grip	C 
Fuel efficiency	D 
Sound (decibel)	72 dB 
Axle position	All axles

