

# Earthmover ( Off-the-Road )



**S-600**

Skidsteer Loaders, Telescopic Forks, etc.  
Tubeless

Size	P.R.	Overall Diameter ( mm )	Section Width ( mm )	Tread Depth ( mm )	Rim	Inflation Pressure ( Kpa )	Load Capacity (kg/10km/h)	LI / SI
<b>10-16.5</b>	10	773	264	19	8.25	520	2135	134A2
<b>12-16.5</b>	12	773	307	19	9.75	550	2865	145A2
<b>5.70-12</b>	6	570	146	14	4.50I	410	660	98A2
<b>23x8.50-12</b>	6	574	213	13	7.00I	340	820	101A2
<b>27x8.50-15</b>	6	678	213	13	7JA	310	1030	109A2
<b>27x10.5-15</b>	8	670	259	18	8.5	359	1250	120A2
<b>14-17.5</b>	14	912	349	19	10.5	550	3875	155A2
<b>15-19.5</b>	14	1019	389	21	11.75	485	4565	160A2



**S-680**

Skidsteer Loaders  
Tubeless

Size	P.R.	Overall Diameter ( mm )	Section Width ( mm )	Tread Depth ( mm )	Rim	Inflation Pressure ( Kpa )	Load Capacity (kg/10km/H)	LI / SI
<b>10-16.5</b>	10	773	264	30	8.25	520	2135	134A2
<b>12-16.5</b>	12	831	307	33	9.75	550	2865	145A2