

Velikosti a specifikace

VELIKOSTI	PR	RYCHLOST	HLOUBKA BĚHOUNU		INDEX ZATÍŽENÍ	MAX. ZATÍŽENÍ	ŠÍŘKA ŘEZU	OA DIA.	STD. STISKNĚTE	STD. RÁFEK	HLUK		MOKRÉ	RRC	ŠTÍTEK Č
			MM	32NDS	S/D	S/D Kgs(Lbs)	MM	MM	KPA(Psi)	PALCE	dB(A)				
295/80R22.5	18	K	19.0	23.9	154/151	3750/3450(8270/7610)	298	1044	900(130)	9.00	73	2	C	C	982391
315/80R22.5	20	K	20.0	25.2	157/154	4125/3750(9090/8270)	312	1076	830(120)	9.00	73	2	C	C	982393
12R22.5	18	K	20.0	25.2	152/149	3550/3250(7830/7160)	300	1084	930(135)	9.00	73	2	C	C	1391231
13R22.5	18	K	21.0	26.5	154/151	3750/3450(8270/7610)	320	1124	830(120)	9.75	73	2	C	C	
13R22.5	20	K	21.0	26.5	156/150	4000/3350(8820/7390)	320	1124	875(127)	9.75	73	2	C	C	982377