

Size	LR/PR	Service index	Fuel Efficiency	Wet Traction	dB/Noise	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
										Single				Dual			
										(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
245/70R17.5	H/16	136/134M	E	D	72/B	13.0	6.75	789	248	2240	4940	850	123	2120	4675	850	123
205/75R17.5	G/14	124/122M(126/124G)	E	D	72/B	12.0	6.00	753	205	1600	3525	750	109	1500	3305	750	109
215/75R17.5	G/14	128/126M	E	D	72/B	13.0	6.00	767	211	1800	3970	760	110	1700	3750	760	110
225/75R17.5	G/14	129/127M	E	D	72/B	13.0	6.75	783	226	1850	4080	725	105	1750	3860	725	105
235/75R17.5	G/14	132/130M	E	D	72/B	14.0	6.75	797	233	2000	4410	775	112	1900	4190	775	112
245/70R19.5	H/16	136/134M	D	D	72/B	13.0	7.50	839	248	2240	4940	830	120	2120	4675	830	120
265/70R19.5	H/16	140/138M	D	D	72/B	13.0	7.50	867	262	2500	5510	775	112	2360	5200	775	112
285/70R19.5	H/16	146/144M	D	D	72/B	13.0	8.25	895	283	3000	6610	850	123	2800	6175	850	123