



MultiAp ECO Z1

Size	LR/PR	Service index	Fuel Efficiency	Wet Traction	dB/Noise	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
										Single				Dual			
										(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
385/55R22.5	L/20	160K(158L)	B	B	73/B	13.0	12.25	996	386	4500	9920	900	130	-	-	-	-
385/65R22.5	L/20	160K	B	C	73/B	13.5	11.75	1072	389	4500	9920	900	130	-	-	-	-
385/65R22.5	N/24	164K	B	C	73/B	13.5	11.75	1072	389	5000	11030	900	130	-	-	-	-
315/70R22.5	L/20	156/150L	B	C	73/B	13.5	9.00	1014	312	4000	8820	900	130	3350	7390	900	130
295/80R22.5	J/18	152/149M	B	C	73/B	14.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	156/153L(154/151M)	B	C	73/B	14.0	9.00	1076	312	4000	8820	850	123	3650	8050	850	123

*Reserves the rights of final interpretation and modification