

Size	LR/PR	Service index	Fuel Efficiency	Wet Traction	dB/Noise	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
										Single				Dual			
										(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
355/50R22.5	L/20	156K(154L)	B	C	74/B	14.0	11.75	928	361	4000	8820	900	130	-	-	-	-
385/55R22.5	L/20	160K(158L)	B	B	74/B	14.0	12.25	996	386	4500	9920	900	130	-	-	-	-
385/65R22.5	L/20	160K(158L)	B	C	74/B	15.0	11.75	1072	389	4500	9920	900	130	-	-	-	-
315/70R22.5	L/20	156/150L	B	C	74/B	15.0	9.00	1014	312	4000	8820	900	130	3350	7390	900	130
295/60R22.5	J/18	150/147K	B	C	74/B	14.5	9.00	926	292	3350	7390	900	131	3075	6780	900	131
315/60R22.5	L/20	150/150L(152/148M)	B	C	74/B	13.5	9.75	950	313	3750	8270	800	130	3350	7390	900	130
295/80R22.5	J/18	154/149M	B	C	74/B	16.0	9.00	1044	298	3750	8270	900	131	3250	7160	900	131
315/80R22.5	J/18	156/153L(154/151M)	B	C	74/B	16.0	9.00	1076	312	4000	8820	850	123	3650	8050	850	123