

TIRE SIZE	PR	TT/TL	LOAD/SPEED INDEX	RIM		INFLATED DIMENSIONS (NO LOAD)		INFLATING PRESSURE (psi)	LOAD CAPACITY PER TIRE (KG)
				RECOM. (INCHES)	PERMITTED (INCHES)	OUTER DIAMETER (MM)	SECTION WIDTH MIN MAX (MM)		
4.00-8	8	TT	94 / A5	3 ¼ I	3.00D	414	115	131	670
5.00-8	10	TT	111 / A5	3.00D	3 ¼ I, 3 ¾ I	467	132	145	1090
18x7-8	16	TT	125 / A5	4.33R	-	462	173	145	1650
6.00-9	12	TT	121 / A5	4.00E	-	540	160	145	1450
21x8-9	14	TT	131 / A5	6.00E	-	535	200	131	1950
6.50-10	12	TT	125 / A5	5.00F	5.50F	588	177	131	1650
23x9-10	20	TT	142 / A5	6.50F	-	595	225	145	2650
7.00-12	14	TT	134 / A5	5.00S	-	672	192	131	2120
27x10-12	14	TT	143 / A5	8.00G	-	690	255	102	2725
23x5-13	10	TT	121 / A5	3,75P	-	635	155	116	1150
8.15-15	14	TT	146 / A5	7.0	-	707	216	145	3000
8.25-15	16	TT	149 / A5	6.5	7	836	234	134	3550