

TIRE SIZE	PR	TT/TL	LOAD / SPEED INDEX	RIMS		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		
				RECOMMENDED (INCH)	PERMITTED (INCH)	OUTER DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOADED RADIUS (MM)	DYNAMIC ROLLING CIRCUMFERENCE (MM)	
8.3-24	✓	8	TT	108 / A6	W7	W6	995	211	455	2965
9.5-24	✓	8	TT	112 / A6	W8	W7	1050	241	481	3129
11.2-24	✓	8	TT	116 / A6	W10	W9	1105	284	503	3293
11.2-28	✓	8	TT	118 / A6	W10	W9	1205	284	554	3591
12.4-24	✓	6	TT	115 / A6	W11	W9, W10	1160	315	525	3457
12.4-24	✓	8	TT	120 / A6	W11	W9, W10	1160	315	525	3457
12.4-24	✓	12	TT	128 / A6	W11	W9, W10	1160	315	525	3457
12.4-28	✓	6	TT	117 / A6	W11	W9, W10	1260	315	576	3755
12.4-28	✓	8	TT	117 / A6	W11	W9, W10	1260	315	576	3755
12.4-32	✓	8	TT	124 / A6	W11	W9, W10	1360	315	626	4053
12.4-36	✓	8	TT	126 / A6	W11	W9, W10	1465	315	678	4366
12.4-36	✓	14	TT	139 / A6	W11	W9, W10	1465	315	678	4366
13.6-24	✓	8	TT	123 / A6	DW12	DW11	1200	345	541	3576
13.6-28	✓	6	TT	121 / A6	W12	W11	1310	345	596	3904
13.6-28	✓	8	TT	125 / A6	W12	W11	1310	345	596	3904
13.6-36	✓	6	TT	125 / A6	W12	W11	1515	345	698	4515
13.6-36	✓	8	TT	129 / A6	W12	W11	1515	345	698	4515
13.6-38	✓	8	TT	131 / A6	W12	W11	1565	345	723	4664
13.6-38	✓	14	TT	142 / A6	W12	W11	1565	345	723	4664
14.00-38	✓	8	TT	131 / A6	W12	W11	1570	350	725	4679
14.00-38	✓	10	TT	136 / A6	W12	W11	1570	350	725	4679
14.9-24	✓	4	TT	112 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	4	TL	112 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	6	TT	123 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	8	TT	128 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	10	TT	134 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	14	TT	142 / A6	W13	W11, W12	1265	378	567	3770
14.9-24	✓	14	TL	142 / A6	W13	W11, W12	1265	378	567	3770
14.9-28	✓	6	TT	125 / A6	W13	W11, W12	1365	378	618	4068
14.9-28	✓	8	TT	130 / A6	W13	W11, W12	1365	378	618	4068
14.9-30	✓	8	TT	131 / A6	W13	W11, W12	1415	378	643	4217
14.9-30	✓	10	TT	135 / A6	W13	W11, W12	1415	378	643	4217
15.5-38	✓	8	TT	133 / A6	W14L	-	1570	394	725	4679
15.5-38	✓	10	TT	138 / A6	W14L	-	1570	394	725	4679
15.5-38	✓	12	TT	142 / A6	W14L	-	1570	394	725	4679
15.5-38	✓	14	TT	145 / A6	W14L	-	1570	394	725	4679
16.9-28	✓	8	TT	135 / A6	W15L	W14L	1435	429	646	4276
16.9-28	✓	10	TT	139 / A6	W15L	W14L	1435	429	646	4276
16.9-28	✓	12	TT	143 / A6	W15L	W14L	1435	429	646	4276
'16.9-28	✓	14	TT	145 / A8	W15L	W14L	1435	429	645,6	4276
16.9-30	✓	8	TT	137 / A6	W15L	W14L	1485	429	671	4425
16.9-30	✓	10	TT	139 / A6	W15L	W14L	1485	429	671	4425
16.9-30	✓	12	TT	143 / A6	W15L	W14L	1485	429	671	4425
16.9-30	✓	14	TT	144 / A6	W15L	W14L	1485	429	671	4425
16.9-34	✓	8	TT	139 / A6	W15L	W14L	1585	429	721	4723
16.9-34	✓	10	TT	142 / A6	W15L	W14L	1585	429	721	4723
16.9-34	✓	12	TT	145 / A6	W15L	W14L	1585	429	721	4723
16.9-34	✓	14	TT	148 / A6	W15L	W14L	1585	429	721	4723
16.9-38	✓	8	TT	141 / A6	W15L	W14L	1685	429	771	5021
16.9-38	✓	10	TT	144 / A6	W15L	W14L	1685	429	771	5021
16.9-38	✓	12	TT	142 / A6	W15L	W14L	1685	429	771	5021
18.4-26	✓	14	TT	149 / A6	W16L	W15L	1450	467	647	4321
18.4-26	✓	12	TT	146 / A6	W16L	W15L	1450	467	647	4321
18.4-26	✓	12	TL	146 / A6	W16L	W15L	1450	467	647	4321
18.4-30	✓	6	TT	134 / A6	W16L	W15L	1550	467	697	4619
18.4-30	✓	8	TT	139 / A6	W16L	W15L	1550	467	697	4619
18.4-30	✓	10	TT	145 / A6	W16L	W15L	1550	467	697	4619
18.4-30	✓	12	TT	149 / A6	W16L	W15L	1550	467	697	4619
18.4-30	✓	14	TT	151 / A6	W16L	W15L	1550	467	697	4619
18.4-34	✓	8	TT	141 / A6	W16L	W15L	1650	467	747	4917
18.4-34	✓	10	TT	146 / A6	W16L	W15L	1650	467	747	4917
18.4-34	✓	12	TT	151 / A6	W16L	W15L	1650	467	747	4917
18.4-34	✓	14	TT	156 / A6	W16L	W15L	1650	467	747	4917
18.4-38	✓	8	TT	143 / A6	W16L	W15L	1750	467	797	5215
18.4-38	✓	10	TT	147 / A6	W16L	W15L	1750	467	797	5215
18.4-38	✓	10	TL	147 / A6	W16L	W15L	1750	467	797	5215
'18.4-38	✓	14	TT	155 / A8	W16L	W15L	1750	467	797	5215