

TIRE SIZE	PR	TT/TL	LOAD / SPEED INDEX	RIMS		INFLATED DIMENSIONS (NO LOAD)		INFLATED DIMENSIONS (W/LOAD)		
				RECOMMENDED (INCH)	PERMITTED (INCH)	OUTER DIAMETER (MM)	SECTION WIDTH (MM)	STATIC LOADED RADIUS (MM)	DYNAMIC ROLLING CIRCUMFERENCE (MM)	
5.50-16	✓	6	TT	86 / A6	4.00E	3.50D, 4.50E	710	150	329	2130
6.00-16	✓	6	TT	86 / A6	4.50E	4.00E, 5.00F	735	165	338	2205
6.50-16	✓	6	TT	91 / A6	4.50E	4.00E, 5K, 5.50F, 5.50F	760	175	350	2280
6.50-16	✓	8	TT	97 / A6	4.50E	4.00E, 5K,5.50F, 5.50F	760	175	350	2280
7.50-16	✓	6	TT	98 / A6	5.50F	5.00F, 5K, 6.00F	805	205	367	2415
7.50-16	✓	8	TT	103 / A6	5.50F	5.00F, 5K, 6.00F	805	205	367	2415
6.00-19	✓	6	TT	93 / A6	4.50E	4.00E, 5.00F	814	165	378	2442
6.50-20	✓	8	TT	108 / A6	5.00F	4.00E, 5.50F	865	165	402	2595
6.50-20	✓	10	TT	115 / A6	5.00F	4.00E, 5.50F	865	165	402	2595
7.50-20	✓	8	TT	108 / A6	5.50F	5.00F	915	214	420	2727
7.50-20	✓	10	TT	115/A6	5.50F	5.00F	915	214	420	2727