

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
			inch	mm	inch	mm	inch	mm	mm	kg	lbs	kmph	mph		bar	psi
24"	12.4-24	8	W 11	1160	45.7	315	12.4	3410	539	1285	2830	40	25	117 A8	2.2	32
24"	12.4-24	12	W 11	1160	45.7	315	12.4	3410	539	1600	3520	40	25	124 A8	3.3	48
24"	13.6-24	12	W 12	1190	46.9	345	13.6	3657	562	1500	3300	40	25	122 A8	2.2	32
24"	14.9-24	8	W 13	1265	49.8	375	14.8	3719	583	1600	3520	40	25	124 A8	1.8	26
24"	14.9-24	12	W 13	1265	49.8	375	14.8	3719	583	2000	4410	40	25	132 A8	2.6	38
24"	16.9-24	8	W 15L	1335	52.6	429	16.9	3950	615	2060	4542	30	19	133 A6	1.7	25
24"	16.9-24	10	W 15L	1335	52.6	429	16.9	3950	615	2240	4940	30	19	136 A6	2.1	29
24"	16.9-24	12	W 15L	1335	52.6	425	16.7	3950	615	2060	4540	40	25	133 A8	2.2	32
24"	16.5/80-24	8	W 15L	1335	52.6	425	16.7	3950	615	1850	4080	40	25	129 A8	1.7	24
24"	16.5/80-24	12	W 15L	1335	52.6	425	16.7	3950	615	2060	4540	40	25	133 A8	2.2	32
26"	13.6-26	8	W 12	1270	50	352	13.9	3657	562	1600	3530	40	25	124 A8	2.39	34
26"	13.6-26	12	W 12	1270	50	352	13.9	3657	562	1900	4188	40	25	130 A8	2.9	42
26"	14.9-26	8	W 13	1315	51.8	385	15.2	3863	608	1650	3640	40	25	125 A8	1.8	26
26"	14.9-26	12	W 13	1315	51.8	385	15.2	3863	608	2000	4410	40	25	132 A8	2.5	36
26"	16.9-26	12	W 15L	1384	54.5	429	16.9	4183	625	2060	4540	40	25	133 A8	1.9	28
26"	16.9-26	14	W 15L	1384	54.5	420	16.5	4183	625	2300	5070	40	25	137 A8	2.4	35
26"	18.4-26	12	W 16L	1450	57.1	420	16.5	4250	650	2650	5840	40	25	142 A8	2.2	32
26"	18.4-26	14	W 16L	1450	57.1	467	18.4	4250	650	3075	6780	40	25	147 A8	2.6	38
26"	23.1-26	12	DW 20 AB	1585	62.4	587	23.1	4615	700	3250	7150	40	25	149 A8	1.7	24
26"	23.1-26	14	DW 20 AB	1585	62.4	587	23.1	4615	700	3550	7850	40	25	152 A8	1.9	28
26"	23.1-26	16	DW 20 AB	1585	62.4	587	23.1	4615	700	3875	8540	40	25	155 A8	2.2	32
26"	23.1-26	18	DW 20 AB	1585	62.4	587	23.1	4615	700	4125	9094	40	25	157 A8	2.4	35
28"	11.2-28	8	W 10	1205	47.4	280	11	3540	565	1120	2470	40	25	112 A8	2.1	30
28"	11.2-28	12	W 10	1205	47.4	280	11	3540	565	1320	2910	40	25	118 A8	2.6	38
28"	12.4-28	6	W 11	1260	49.6	320	12.6	3704	889	1150	2540	40	25	113 A8	1.7	24
28"	12.4-28	8	W 11	1260	49.6	320	12.6	3704	889	1400	3090	40	25	120 A8	2.2	32
28"	12.4-28	12	W 11	1260	49.6	320	12.6	3704	889	1450	3200	40	25	121 A8	2.4	35
28"	13.6-28	8	W 12	1310	51.6	345	13.6	3851	610	1500	3300	40	25	122 A8	1.9	28
28"	13.6-28	12	W 12	1310	51.6	345	13.6	3851	610	1900	4180	40	25	130 A8	2.9	42
28"	14.9-28	8	W 13	1361	53.6	375	14.8	4013	634	1700	3740	40	25	126 A8	1.8	26
28"	14.9-28	12	W 13	1361	53.6	375	14.8	4013	634	2060	4540	40	25	133 A8	2.6	38
28"	14.9-28	14	W 13	1361	53.6	375	14.8	4013	634	2120	4674	40	25	134 A8	3.3	48
28"	16.9-28	8	W 15L	1435	56.5	430	16.9	4310	655	1950	4300	40	25	131 A8	1.65	24
28"	16.9-28	10	W 15L	1435	56.5	430	16.9	4310	655	2120	4680	40	25	134 A8	1.9	28
28"	16.9-28	12	W 15L	1435	56.5	430	16.9	4310	655	2240	4930	40	25	136 A8	2.1	30
28"	16.9-28	16	W 15L	1435	56.5	430	16.9	4310	655	2500	5510	40	25	140 A8	2.6	37
30"	14.9-30	8	W 11, W 12	1415	55.7	378	14.9	4316	659	1750	3860	40	25	127 A8	1.8	26
30"	14.9-30	10	W 11, W 12	1415	55.7	378	14.9	4316	659	1950	4300	40	25	131 A8	2.2	32
30"	14.9-30	12	W 11, W 12	1415	55.7	378	14.9	4316	659	2100	4630	40	25	134 A8	2.5	36
30"	16.9-30	8	W 15L	1485	58.5	430	16.9	4366	688	2000	4400	40	25	132 A8	1.65	24
30"	16.9-30	10	W 15L	1485	58.5	430	16.9	4366	688	2240	4940	40	25	136 A8	1.9	28
30"	16.9-30	12	W 15L	1485	58.5	430	16.9	4366	688	2500	5520	40	25	140 A8	2.3	34
30"	16.9-30	14	W 15L	1485	58.5	430	16.9	4366	688	2725	6000	40	25	143 A8	2.8	40
30"	18.4-30	8	W 16L	1545	60.8	460	18.1	4542	714	2180	4800	40	25	135 A8	1.4	20
30"	18.4-30	12	W 16L	1545	60.8	460	18.1	4542	714	2900	6400	40	25	145 A8	2.2	32
30"	18.4-30	14	W 16L	1545	60.8	460	18.1	4542	714	3250	7160	40	25	149 A8	2.5	36