

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
				mm	inch	mm	inch			mm	mm	kg	lbs		kmph	mph
8"	4.00-8	4	3.0 D	418	16.5	114	4.5	1220	185	272	600	30	19	63 A6	3.3	48
10"	4.00-10	4	3.0 D	466	18.3	110	4.3	1364	217	290	640	30	19	65 A6	2.75	40
10"	5.00-10	4	3.0 D	512	20.1	140	5.5	1508	235	305	670	30	19	67 A6	2.25	33
12"	4.00-12	4	3.0 D	525	20.7	120	4.7	1546	241	210	460	30	19	54 A6	1.5	22
12"	5.00-12	6	3.0 D	580	22.8	130	5.1	1731	271	307	580	30	19	67 A6	2.8	41
12"	5.00-12	6	3.0 D	580	22.8	130	5.1	1731	271	307	580	30	19	67 A6	2.8	41
12"	6.00-12	6	4	630	24.8	160	6.3	1901	293	400	882	30	19	76 A6	2.6	38
12"	6-12	6	4	630	24.8	160	6.3	1901	293	400	882	30	19	76 A6	2.6	38
12"	6.00-12	6	4	630	24.8	160	6.3	1901	293	400	882	30	19	76 A6	2.6	38
12"	6.5/80-12	6	5	569	22.4	162	6.4	1685	260	505	1110	30	19	85 A6	3.6	52
12"	7-12	6	6	687	27	200	7.9	2007	305	487	1070	30	19	83 A6	2.5	36
12"	7-13	8	6	687	27	187	7.9	2007	305	615	1356	30	19	91 A6	3.3	47
13"	6.5/80-13	6	5	642	25.3	171	6.7	1765	280	770	1700	30	19	99 A6	3.6	52
14"	6-14	6	5.0 JA, 5.0 KB	655	25.8	157	6.2	1965		387	850	30	19	75 A6	2.2	32
14"	7-14	6	6	691	27.2	180	7.2	2057	330	450	990	30	19	80 A6	2.5	36
15"	5.00-15	6	4	657	25.8	145	5.7	1956	305	387	850	30	19	75 A6	3.6	51
15"	5.90-15	6	4.5	663	26.1	160	6.3	1976	310	825	1820	30	19	101 A6	2.1	30
15"	6.5/80-15	6	5	683	26.9	170	6.7	1976	310	840	1850	30	19	101 A6	3.6	52
15"	6.5/80-16	12	5.1	664	26.1	164	6.5	1977	311	1400	3085	30	19	120 A6	5.8	84
15"	690x180-15	6	5	690	27.2	176	6.9	2055	322	810	1790	30	19	101 A6	2.3	36
15"	7.00-15	8	5.5	715	28.1	183	7.2	2126	331	1050	2310	30	19	110 A6	3.6	52
15"	7.5L-15	8	6	765	31.2	210	8.2	2286	356	890	1960	30	19	104 A6	3.7	54
15"	7.50-15	8	6	770	30.3	208	8.1	2308	359	1285	2830	30	19	117 A6	5	72
15"	8.0/75-15	6	6.5	708	27.9	199	7.8	2093	326	800	1760	30	19	100 A6	2.5	36
16"	4.00-16	6	3.0 D	628	24.7	110	4.3	1835	307	530	1168	30	19	86 A6	3.25	47
16"	4.50-16	6	3.0 D	655	25.8	122	4.8	1952	311	365	800	30	19	73 A6	3.2	47
16"	6.00-16	8	5	735	28.9	165	6.5	2100	330	670	1480	30	19	94 A6	4.5	65
16"	6.50-16	8	4.5	765	30.1	180	7	2184	330	1035	2280	30	19	109 A6	3.75	54
16"	6.50-16	10	4.5	765	30.1	180	7	2184	330	1150	2535	30	19	113 A6	4	58
16"	7-16	6	6	742	29.2	183	7.2	2196	341	500	1100	30	19	84 A6	2.5	36
16"	7.50-16	8	5.5 F	800	31.5	205	8.1	2368	367	875	1930	30	19	103 A6	3.7	54
16"	7.50-16	12	5.5 F	800	31.5	205	8.1	2368	367	1150	2535	30	19	113 A6	4.96	72
16"	8-16	6	6	785	30.9	200	7.9	2360	366	615	1360	30	19	91 A6	1.9	28
16"	8-16	8	6	785	30.9	200	7.9	2360	366	750	1650	30	19	98 A6	2.6	38
16"	8.25-16	8	7	848	33.3	229	9	2540	354	1400	3090	30	19	120 A6	3.1	45
16"	9.5-16	8	W 8L	840	33.1	235	9.3	2502	384	850	1870	30	19	102 A6	2.8	41
16"	9.0/75-16	8	8	774	30.5	229	9	2330	355	1060	2337	30	19	110 A6	4.4	63
16"	250/80-16	8	8	816	32.1	240	9.4	2412	369	1285	2830	30	19	117 A6	2.8	41
18"	7.50-18	8	6	854	33.6	214	8.4	2540	406	950	2090	30	19	106 A6	3.7	54
18"	7.50-18	12	6	854	33.6	214	8.4	2540	406	1285	2832	30	19	117 A6	5.5	80
18"	250/80-18	10	8	857	33.7	251	9.9	2667	406	1360	3000	30	19	119 A6	2.8	41
18"	8-18	8	W 7	845	33.3	190	7.5	2515	390	800	1760	30	19	100 A6	2.6	38
18"	9.5-18	8	W 8	900	35.4	235	9.3	2692	420	925	2040	30	19	105 A6	3	43
19"	4.50-19	6	3.0D	736	29	120	4.7	2171	339	487	1074	30	19	83 A6	4.4	64
20"	7.50-20	8	5.5F	904	35.6	209	8.2	2695	422	980	2160	30	19	107 A6	3.2	46