

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
				mm	inch	mm	inch			mm	mm	kg	lbs		kmph	mph
20"	9.5-20	6	W 8	950	37.4	235	9.25	2942	449	825	1820	30	19	101 A6	2.1	30
20"	9.5-20	8	W 8	950	37.4	235	9.25	2942	449	975	2150	30	19	107 A6	2.8	40
20"	11.2-20	8	W 10	1020	40.2	290	11.4	3000	476	1090	2400	30	19	111 A6	2.4	35
22"	8.3-22	8	W 7	945	37.2	205	8	2778	444	900	1980	30	19	104 A6	3.2	46
22"	9.5-22	8	W 8	1005	39.6	235	9.3	2955	469	1060	2340	30	19	110 A6	2.9	42
22"	9.5-22	12	W 8	1005	39.6	235	9.3	2955	469	1320	2910	30	19	118 A6	4.1	60
24"	8.3-24	6	W 7	995	39.2	210	8.3	2925	469	825	1820	30	19	101 A6	2.4	35
24"	8.3-24	8	W 7	995	39.2	210	8.3	2925	469	925	2040	30	19	105 A6	3.1	45
24"	9.5-24	6	W 8	1055	41.5	230	9.1	3105	495	950	2090	30	19	106 A6	2.1	30
24"	9.5-24	8	W 8	1055	41.5	230	9.1	3105	495	1120	2470	30	19	112 A6	2.8	41
24"	9.5-24	12	W 8	1055	41.5	230	9.1	3105	495	1400	3086	30	19	120 A6	3.45	50
24"	11.2-24	8	W 10	1090	42.9	280	11	3205	509	1250	2760	30	19	116 A6	2.4	35
24"	11.2-24	10	W 10	1090	42.9	280	11	3205	509	1400	3086	30	19	120 A6	3	43
24"	11.2-24	12	W 10	1090	42.9	280	11	3205	509	1550	3420	30	19	123 A6	3.6	52
28"	8.3-28	8	W 7	1104	43.4	213	8.4	3246	523	1000	2200	30	19	109 A6	3.2	46
30"	7.2-30	6	W 6	1095	43.1	185	7.3	3219	523	690	1520	30	19	95 A6	2.3	33
32"	8.3-32	8	W 7	1195	47	211	8.3	3585	572	1090	2400	30	19	111 A6	3.2	46
32"	9.5-32	8	W 8	1255	49.4	235	9.3	3686	594	1060	2340	30	19	110 A6	2.1	30
32"	12.4-32	8	W 11	1360	53.5	320	12.6	3998	636	1650	3640	30	19	125 A6	2.2	32
32"	12.4-32	10	W 11	1360	53.5	320	12.6	3998	636	1800	3970	30	19	128 A6	2.8	41
36"	12.4-36	8	W 11	1465	57.7	320	12.6	4307	691	1750	3860	30	19	127 A6	2.3	33
36"	12.4-36	12	W 11	1465	57.7	320	12.6	4307	691	2180	4810	30	19	135 A6	3.5	51
36"	13.6-36	8	W 12	1515	59.6	345	13.6	4454	713	1950	4300	30	19	131 A6	2.1	30
36"	13.6-36	12	W 12	1515	59.6	345	13.6	4454	713	2300	5070	30	19	137 A6	2.9	42
36"	7/7.2-36	8	W 6	1255	49.4	183	7.2	3702	577	1000	2205	30	19	108 A6	3.7	54
36"	9.5-36	8	W 8	1360	53.5	235	9.3	4000	646	1250	2760	30	19	116 A6	2.76	40
36"	9.5-36	10	W 8	1360	53.5	235	9.3	4000	646	1500	3310	30	19	122 A6	3.5	51
36"	9.5-36	12	W 8	1360	53.5	235	9.3	4000	646	1800	3968	30	19	128 A6	3.79	55
38"	11.2-38	8	W 10	1445	56.9	284	11.2	4400	675	1500	3310	30	19	122 A6	2.3	33
38"	11.2-38	12	W 10	1445	56.9	284	11.2	4400	675	1800	3968	30	19	128 A6	3.25	47
38"	12.4-38	6	W 11	1215	60	315	12.4	4670	718	1585	2830	30	19	117 A6	1.8	26
38"	12.4-38	8	W 11	1215	60	315	12.4	4670	718	1750	3860	30	19	127 A6	2.3	33
38"	12.4-38	10	W 11	1215	60	315	12.4	4670	718	1900	4188	30	19	130 A6	2.75	40
38"	12.4-38	12	W 11	1215	60	310	12.4	4670	718	2120	4670	30	19	134 A6	3.3	48
38"	12.4-38	14	W 11	1215	60	310	12.4	4670	718	2360	5200	30	19	138 A6	3.7	54