

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
				mm	inch	mm	inch			mm	mm	kg	lbs		kmph	mph
12"	4.00-12	4	3.0 D	530	20.9	110	4.3	1573	255	200	440	40	25	52 A8	3.4	49
15"	4.00-15	4	3.0 D	610	24	110	4.3	1854	295	265	580	40	25	62 A8	3.6	52
15"	5.00-15	6	4.0 E	655	25.8	140	5.5	1951	307	400	880	40	25	76 A8	4.15	60
15"	7.5L-15	6	6	745	29.3	200	7.9	2212	342	650	1430	40	25	93 A8	3	44
15"	9.5L-15	8	7	780	30.7	240	9.4	2330	359	850	1870	40	25	102 A8	3.3	48
15"	11L-15	8	8 LB	815	32.1	279	11	2440	373	950	2090	40	25	106 A8	3	44
15"	11L-15	12	8 LB	795	32.1	279	11	2440	373	1215	2678	40	25	115 A8	4	58
16"	5.50-16	8	4.0 E	700	27.6	150	5.9	2116	332	545	1200	40	25	87 A8	4.5	65
16"	6.00-16	6	4.5 E	735	28.9	165	6.5	2190	346	515	1140	40	25	85 A8	3.6	52
16"	6.00-16	8	4.5 E	735	28.9	165	6.5	2190	346	615	1350	40	25	91 A8	4.7	68
16"	6.50-16	6	4.5 E	765	30.1	180	7.1	2280	359	560	1230	40	25	88 A8	3.3	48
16"	6.50-16	8	4.5 E	765	30.1	180	7.1	2280	359	650	1430	40	25	93 A8	4.1	60
16"	7.50-16	8	5.5 F	810	31.9	207	8.1	2414	379	775	1710	40	25	99 A8	3.85	56
16"	7.50-16	12	5.5 F	810	31.9	207	8.1	2414	379	975	2150	40	25	107 A8	5.4	78
16"	9.00-16	10	W 8	855	33.7	250	9.8	2548	398	1090	2400	40	25	111 A8	4.15	60
16"	9.00-16	12	W 8	855	33.7	250	9.8	2548	398	1250	2760	40	25	116 A8	4.85	70
16"	10.00-16	8	W 8	890	35	275	10.8	2682	410	1060	2340	40	25	110 A8	3	44
16"	10.00-16	10	W 8	890	35	275	10.8	2682	410	1215	2680	40	25	115 A8	3.8	55
16"	10.00-16	12	W 8	890	35	275	10.8	2682	410	1320	2910	40	25	118 A8	4.5	65
16"	11.00-16	10	W 10L	970	38.2	310	12.2	2890	448	1360	3000	40	25	119 A8	3.5	51
16"	11.00-16	12	W 10L	970	38.2	310	12.2	2890	448	1550	3420	40	25	123 A8	4.15	60
18"	7.50-18	8	5.5 F	860	33.9	205	8.1	2562	404	850	1870	40	25	102 A8	3.85	56
18"	7.50-18	12	5.5 F	860	33.9	205	8.1	2562	404	1150	2540	40	25	113 A8	5.5	80
19"	4.00-19	4	3.0 D	715	28.1	115	4.5	2145	343	325	715	40	25	69 A8	3.6	52
19"	4.00-19	6	3.0 D	715	28.1	115	4.5	2145	343	355	780	40	25	72 A8	4.2	61
19"	4.00-19	8	3.0 D	715	28.1	115	4.5	2145	343	475	1047	40	25	82 A8	4.48	65
19"	6.00-19	8	4.5 E	815	32.1	165	6.5	2445	386	600	1320	40	25	90 A8	3.9	56
20"	6.50-20	8	5.0 F	860	33.9	180	7.1	2565	400	800	1760	40	25	100 A8	4.1	60
20"	7.50-20	8	5.5 F	915	36	205	8.1	2725	431	925	2040	40	25	105 A8	3.85	56
20"	7.50-20	12	5.5 F	915	36	205	8.1	2725	431	1150	2535	40	25	113 A8	5.5	79