

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
				mm	inch	mm	inch			mm	mm	kg	lbs		kmph	mph
12"	7.00-12	8	4.25	665	26.2	185	7.3	1948	295	825	1820	40	25	101 A8	3.1	45
12"	10.0/80-12	8	9	700	27.6	264	10.4	2080	312	1250	2755	40	25	116 A8	3.1	45
12"	10.0/80-12	10	9	700	27.6	264	10.4	2080	312	1450	3195	40	25	121 A8	3.9	56
12"	10.0/80-12	12	9	700	27.6	264	10.4	2080	312	1650	3640	40	25	125 A8	4.7	68
15.3"	10.0/75-15.3	12	9	760	29.9	264	10.4	2227	343	1700	3747	40	25	126 A8	4.70	68
15.3"	10.0/75-15.3	14	9	760	29.9	264	10.4	2227	343	1900	4190	40	25	130 A8	5.5	80
15.3"	10.0/75-15.3	16	9	760	29.9	264	10.4	2227	343	2060	4540	40	25	133 A8	6.3	91
15.3"	10.0/75-15.3	18	9	760	29.9	264	10.4	2227	343	2180	4800	40	25	135 A8	7.1	103
15.3"	10.0/75-15.3	22	9	760	29.9	264	10.4	2227	343	2300	5070	40	25	137 A8	7.1	103
15.3"	11.5/80-15.3	12	9	845	33.3	290	11.4	2473	370	2180	4805	40	25	135 A8	4.1	59
15.3"	11.5/80-15.3	14	9	845	33.3	290	11.4	2473	370	2430	5360	40	25	139 A8	4.75	69
15.3"	11.5/80-15.3	16	9	845	33.3	290	11.4	2473	370	2575	5680	40	25	141 A8	5.4	78
15.3"	11.5/80-15.3	18	9	845	33.3	290	11.4	2473	370	2725	6000	40	25	143 A8	6.1	88
15.3"	11.5/80-15.3	22	9	845	33.3	290	11.4	2473	370	2800	6170	40	25	144 A8	6.1	88
15.3"	12.5/80-15.3	14	9	885	34.8	310	12.2	2591	387	2650	5840	40	25	142 A8	4.3	62
15.3"	12.5/80-15.3	16	9	885	34.8	310	12.2	2591	387	2800	6170	40	25	144 A8	4.9	71
15.3"	12.5/80-15.3	18	9	885	34.8	310	12.2	2591	387	3000	6610	40	25	146 A8	5.5	80
15.5"	280/60-15.5	14	8	730	28.7	272	10.7	2140	324	1215	2680	40	25	115 A8	2.4	35
16"	10.5/65-16	10	W 9	755	29.7	274	10.8	2212	355	1550	3420	40	25	123 A8	3.8	55
16"	10.5/65-16	12	W 9	755	29.7	274	10.8	2212	355	1750	3858	40	25	127 A8	4.7	68
16"	10.5/65-16	14	W 9	755	29.7	274	10.8	2212	355	1900	4190	40	25	130 A8	5.3	77
16"	360/70-16	10	11	910	35.8	357	14	2697	380	2300	5070	40	25	137 A8	2.4	35
16"	13.0/70-16	12	11	770	30.3	336	13.2	2261	356	2240	4930	40	25	136 A8	5.7	83
18"	13.0/65-18	14	11	890	35	330	13	2608	395	2575	5680	40	25	141 A8	4.3	62
18"	13.0/65-18	16	11	890	35	330	13	2608	395	2800	6170	40	25	144 A8	4.9	71
18"	340/70-18	16	11	902	35.5	342	13.4	2642	410	3650	8050	40	25	153 A8	4.9	71
18"	12.5/80-18	12	9	965	38	308	12.1	2827	432	2650	5840	40	25	142 A8	3.7	54
18"	12.5/80-18	14	9	965	38	308	12.1	2827	432	2900	6390	40	25	145 A8	4.3	62
18"	12.5/80-18	16	9	965	38	308	12.1	2827	432	3150	6940	40	25	148 A8	4.9	71
18"	12.5/80-18	18	9	965	38	308	12.1	2827	432	3350	7380	40	25	150 A8	5.5	80