

Bead Dia	Size	Ply Rating	Stand Rim	Overall Diameter		Section Width		R.C	SLR	Loading Capacity		Speed		Si/Li index	Inflation pressure	
				inch	mm	mm	inch			mm	mm	kg	lbs		kmph	mph
15.3"	10.0/75-15.3	12	9	774	30.5	258	10.2	2310	355	1700	3740	40	25	126 A8	4.7	68
15.3"	10.0/75-15.3	14	9	774	30.5	258	10.2	2310	355	1900	4180	40	25	130 A8	5.5	80
15.3"	10.0/75-15.3	16	9	774	30.5	258	10.2	2310	355	2060	4540	40	25	133 A8	6.3	91
15.3"	11.5/80-15.3	14	9	868	34.2	292	11.5	2578	393	2430	5350	40	25	139 A8	4.75	69
15.3"	11.5/80-15.3	16	9	868	34.2	292	11.5	2578	393	2575	5680	40	25	141 A8	5.4	78
15.3"	11.5/80-15.3	18	9	868	34.2	292	11.5	2578	393	2725	6010	40	25	143 A8	6	87
18"	10.5-18	12	9	905	35.6	270	10.6	2700	415	2180	4800	40	25	135 A8	4.5	65
18"	12.5-18	12	11	950	37.4	290	11.4	2940	450	2240	4940	40	25	136 A8	3.5	51
18"	12.5-18	14	11	950	37.4	290	11.4	2940	450	2430	5350	40	25	139 A8	4	58
18"	12.5-18	16	11	950	37.4	290	11.5	2940	450	2900	6390	40	25	145 A8	4.3	62
20"	12.5-20	14	11	1040	40.9	320	12.6	3090	475	2500	5510	40	25	140 A8	4	58
20"	12.5-20	16	11	1040	40.9	320	12.6	3090	475	2725	6000	40	25	143 A8	4.5	65
20"	16.0/70-20	14	13 SDC	1128	44.4	405	15.9	3350	490	3550	7830	40	25	152 A8	3.5	51
20"	16.0/70-20	16	13 SDC	1128	44.4	405	15.9	3350	490	3875	8540	40	25	155 A8	4	58
24"	16.0/70-24	14	13 SBL	1180	46.5	405	15.9	3460	546	3550	7830	40	25	152 A8	4	58
24"	16.0/70-24	16	13 SBL	1180	46.5	405	15.9	3460	546	3875	8540	40	25	155 A8	4.5	65