

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		IP		OTD mm
								Single	Dual	kpa	Psi	
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575/5675	2430/5355	790	115	16.5
9.00R20	144/142L	16	7.00	7.00T,7.50	259	1019	471	2800/6175	2650/5840	900	130	16.5
10.00R20	146/143L	16	7.50	7.50V,8.00	278	1054	486	3000/6610	2725/6005	830	120	17.5
10.00R20	149/146L	18	7.50	7.50V,8.00	278	1054	486	3250/7160	3000/6610	930	135	17.5
10.00R20	149/146K	18	7.50	7.50V,8.00	278	1054	486	3250/7160	3000/6610	930	135	17.5
11.00R20	150/147L	16	8.00	8.50,8.00V	293	1085	499	3350/7390	3075/6780	830	120	18.5
11.00R20	152/149L	18	8.00	8.50,8.00V	293	1085	499	3550/7830	3250/7160	930	135	18.5
12.00R20	154/151L	18	8.50	8.50V,9.00	315	1125	516	3750/8270	3450/7610	830	120	18.5
10R22.5	141/139M	14	7.50	6.75	254	1019	476	2575/5675	2430/5355	790	115	20.5
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800/6175	2650/5840	720	105	22
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000/6610	2725/6005	830	120	22
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350/7390	3075/6780	830	120	22.0
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550/7830	3250/7160	930	135	22.0
13R22.5	156/153L	18	9.75	9.00	320	1124	521	4000/8820	3650/8050	875	127	22.0
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000/6610	2725/6005	720	105	22
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250/7160	3000/6610	830	120	22.0
295/75R22.5	144/141M	14	9.00	8.25	298	1014	474	2800/6175	2575/5675	760	110	22.0
295/75R22.5	146/143L	16	9.00	8.25	298	1014	474	3000/6610	2725/6005	830	120	22.0
285/75R24.5	144/141M	14	8.25	-	283	1050	493	2800/6175	2575/5675	760	110	22.0
285/75R24.5	147/144L	16	8.25	-	283	1050	493	3075/6780	2800/6175	830	120	22.0
265/70R19.5	140/138L	14	7.50	8.25	262	867	402	2500/5510	2360/5200	850	123	15.0
265/70R19.5	143/141J	18	7.50	8.25	262	867	402	2725/6005	2575/5675	850	123	15.0