

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		
								Single	Dual	kg
9.00R20	141/139L	14	7.00	7.00T,7.50	259	1019	471	2575/5675	2430/5355	79
9.00R20	144/142K	16	7.00	7.00T,7.50	259	1019	471	2800/6175	2650/5840	90
11R22.5	144/142M	14	8.25	7.50	279	1054	491	2800/6175	2650/5840	72
11R22.5	146/143M	16	8.25	7.50	279	1054	491	3000/6610	2725/6005	83
11R22.5	148/144M	16+	8.25	7.50	279	1054	491	3000/6610	2630/5800	83
12R22.5	150/147L	16	9.00	8.25	300	1085	504	3350/7390	3075/6780	83
12R22.5	152/149K	18	9.00	8.25	300	1085	504	3550/7830	3250/7160	93
11R24.5	146/143M	14	8.25	7.50	279	1104	516	3000/6610	2725/6005	72
11R24.5	149/146M	16	8.25	7.50	279	1104	516	3250/7160	3000/6610	83
295/80R22.5	152/148M	16	9.00	8.25	298	1044	487	3550/7825	3150/6945	85
295/80R22.5	152/149L	18	9.00	8.25	298	1044	487	3550/7825	3250/7160	90
315/80R22.5	151/148M	16	9.00	9.75	312	1076	500	3450/7610	3150/6940	76
315/80R22.5	154/151M	18	9.00	9.75	312	1076	500	3750/8270	3450/7610	83
315/80R22.5	157/154L	20	9.00	9.75	312	1076	500	4125/9090	3750/8270	90
295/75R22.5	144/141M	14	9.00	8.25	298	1014	474	2800/6175	2575/5675	76
295/75R22.5	146/143M	16	9.00	8.25	298	1014	474	3000/6610	2725/6005	83