

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		
								Single	Dual	kp
8.25R16LT	126/122M	14	6.50H	6.00G,6.50	235	855	397	1700/3750	1500/3305	67
215/75R17.5	126/124M	14	6	6.75	211	767	359	1700/3750	1600/3530	70
215/75R17.5	127/124M	16	6	6.75	211	767	359	1750/3860	1600/3530	83
215/75R17.5	135/133L	16	6	6.75	211	767	359	2180/4805	2060/4540	86
215/75R17.5	136/134J	18	6	6.75	211	767	359	2240/4940	2120/4675	89
235/75R17.5	132/129M	16	6.75	7.5	233	797	372	2000/4410	1850/4080	83
235/75R17.5	141/140J	16	6.75	7.5	233	797	372	2575/5675	2500/5510	85
235/75R17.5	143/141J	18	6.75	7.5	233	797	372	2725/6005	2575/5675	86
225/70R19.5	125/123M	12	6.75	6	226	811	382	1650/3640	1550/3415	66
225/70R19.5	128/126L	14	6.75	6	226	811	382	1800/3970	1700/3750	76
225/70R19.5	143/141J	18	6.75	6	226	811	382	2725/6005	2575/5675	86
245/70R19.5	133/131L	14	7.5	6.75	248	839	391	2060/4540	1950/4300	76
245/70R19.5	135/133L	16	7.5	6.75	248	839	391	2180/4805	2060/4540	83
245/70R19.5	136/134M	16	7.5	6.75	248	839	391	2240/4940	2120/4675	83
245/70R19.5	141/140J	18	7.5	6.75	248	839	391	2575/5675	2500/5510	85