

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		
								Single	Dual	kg
295/80R22.5	152/148M	16	9	8.25	298	1044	487	3550/7825	3150/6945	85
295/80R22.5	152/148M	16	9	8.25	298	1044	487	3550/7825	3150/6945	85
295/80R22.5	154/151M	18	9	8.25	298	1044	487	3750/8270	3450/7610	90
295/80R22.5	154/151M	18	9	8.25	298	1044	487	3750/8270	3450/7610	90
315/80R22.5	154/151M	18	9	9.75	312	1076	500	3750/8270	3450/7610	83
315/80R22.5	154/151M	18	9	9.75	312	1076	500	3750/8270	3450/7610	83
315/80R22.5	157/154L	20	9	9.75	312	1076	500	4125/9090	3750/8270	90
315/80R22.5	157/154L	20	9	9.75	312	1076	500	4125/9090	3750/8270	90
285/70R19.5	140/137M	14	8.25	9	283	895	413	2500/5510	2300/5070	76
285/70R19.5	144/142M	16	8.25	9	283	895	413	2800/6175	2650/5840	83
285/70R19.5	146/144L	18	8.25	9	283	895	413	3000/6610	2800/6175	85
285/70R19.5	146/144L	18	8.25	9	283	895	413	3000/6610	2800/6175	85
315/70R22.5	149/146M	16	9	9.75	312	1014	469	3250/7160	3000/6610	76
315/70R22.5	151/148M	18	9	9.75	312	1014	469	3450/7610	3150/6940	83
315/70R22.5	152/148M	16	9	9.75	312	1014	469	3550/7830	3150/6940	83
315/70R22.5	152/148M	16	9	9.75	312	1014	469	3550/7830	3150/6940	83