

Size	LI/SS	PR	Rim size	Rim allowance	Inflated Section width mm	Overall diameter mm	Radius under load mm	Load capacity kg/lbs		
								Single	Dual	kp
12R22.5	150/147L	16	9	8.25	300	1085	504	3350/7390	3075/6780	83
12R22.5	152/149K	18	9	8.25	300	1085	504	3550/7830	3250/7160	93
275/80R22.5	147/144M	16	8.25	7.5	276	1012	473	3075/6780	2800/6175	83
275/80R22.5	149/146M	16	8.25	7.5	276	1012	473	3250/7160	3000/6610	85
275/80R22.5	149/146L	18	8.25	7.5	276	1012	473	3250/7160	3000/6610	90
295/80R22.5	150/147M	16	9	8.25	298	1044	487	3350/7390	3075/6780	83
295/80R22.5	152/148M	16	9	8.25	298	1044	487	3550/7830	3150/6940	85
295/80R22.5	152/149M	18	9	8.25	298	1044	487	3550/7830	3250/7160	90
295/80R22.5	154/149M	18	9	8.25	298	1044	487	3750/8270	3250/7160	90
315/80R22.5	154/151M	18	9	9.75	312	1076	500	3750/8270	3450/7610	83
315/80R22.5	157/154L	20	9	9.75	312	1076	500	4125/9090	3750/8270	90
295/60R22.5	150/147K	18	9	9.75	292	926	436	3350/7390	3075/6780	90