



FL 18

FL 18 is a high flotation implement tyre suitable for both drive and free wheel application. With rounded shoulders the tyre causes minimal possible damage to sensitive surfaces. It is built for high load carrying capacity and minimal possible soil compaction. Its suited for use in agricultural implements such as balers, trailers, planters, seeders etc.



TRA Code



Speed Index




Round Baler



Square Baler



Trailer



Planter



Seeder

Tyre Size	Rim Width (inch)	Unloaded Dimensions ± 2%				PR	Load index / Speed symbol	Type	Inf. Pr	Recommended Max Load (kg) / Speed (kmph)							
		SW	OD	SLR	RC					Free Rolling				Drive Wheel			
										10	25	40	50	10	25	40	50
		REC	mm	mm	mm					mm	bar	kmph	kmph	kmph	kmph	kmph	kmph
	in	in	in	in	p.s.i	6 mph	16 mph	25 mph	31 mph	6 mph	16 mph	25 mph	31 mph				
10.0/75-15.3 (260/75-15.3)	9	290	800	352	2325	-	131A8-127B/	TL	5.5	2730	2320	1950	1755	1905	1620	1360	1225
		11.4	31.5	13.9	91.5		119A8-115B		80	6020	5115	4300	3870	4200	3570	3000	2700
11.5/80-15.3 (300/80-15.3)	9	312	870	383	2529	-	138A8-134B/	TL	3.6	3305	2810	2360	2125	2380	2025	1700	1530
		12.3	34.3	15.1	99.6		126A8-122B		52	7290	6195	5205	4685	5250	4465	3750	3375
380/55-17	13	408	872	384	2534	-	138A8/125A8	TL	2.8	3305	2810	2360	2125	2310	1965	1650	1485
		16.1	34.3	15.1	99.8				41	7290	6195	5205	4685	5095	4335	3640	3275
520/50-17	16	513	961	419	2903	-	159B/147B	TL	4.0	6740	5730	4815	4375	4740	4030	3385	3075
		20.2	37.8	16.5	114.3				58	14860	12635	10615	9645	10450	8885	7465	6780
425/70-18	13.00	445	1050	480	3185	14	155B/143B	TL	3.5	5970	5075	4265	3875	4200	3570	3000	2725
		17.4	41.0	18.7	124.2				51.0	13165	11190	9405	8545	9260	7870	6615	6010