



## IM 117

The IM 117 is a value engineered tyre for modern farming implements. tyre has been engineered to offer low soil compaction and high load carrying capacity. The robust shoulder design provides stability and traction while being used in the field.



TRA Code



Speed Index



Trailer



Round Baler



Wagon

Tyre Size	Rim Width (inch)	Unloaded Dimensions ± 2%				PR	Load index / Speed symbol	TYPE	Recommended Max Load (kg/lbs)					
		SW	OD	SLR	RC				Inf. Pr	Free rolling Wheel / Speed				
		mm	mm	mm	mm					bar	10 kmph	25 kmph	30 kmph	40 kmph
		in	in	in	in					p.s.i	6 mph	15 mph	19 mph	25 mph
10.0/80-12	9	250	714	313	2081	6	110 A8	TL	<b>2.3</b>	1485	1260	1185	<b>1060</b>	
						8	116 A8	TL	<b>33</b>	3275	2780	2615	<b>2335</b>	
		9.843	28.11	12.32	81.93	10	121 A8	TL	<b>45</b>	3860	3285	3085	<b>2755</b>	
10.0/75-15.3	9	265	758	338	2198	8	119 A8	TL	<b>3.1</b>	1905	1620	1525	<b>1360</b>	
						10	123 A8	TL	<b>45</b>	4200	3570	3365	<b>3000</b>	
						12	126 A8	TL	<b>3.9</b>	2170	1845	1735	<b>1550</b>	
		10.4	29.8	13.3	86.5	14	130 A8	TL	<b>57</b>	4785	4070	3825	<b>3420</b>	
						18	135 A8	TL	<b>4.7</b>	2380	2025	1905	<b>1700</b>	
										<b>68</b>	5250	4465	4200	<b>3750</b>
11.5/80-15.3	9	295	835	370	2476	10	131 A8	TL	<b>5.5</b>	2660	2260	2130	<b>1900</b>	
						12	135 A8	TL	<b>7.1</b>	3050	2595	2440	<b>2180</b>	
						14	139 A8	TL	<b>103</b>	6725	5720	5380	<b>4805</b>	
		11.6	32.9	14.6	97.5	16	141 A8	TL	<b>3.4</b>	2730	2320	2185	<b>1950</b>	
						18	143 A8	TL	<b>49</b>	6020	5115	4820	<b>4300</b>	
										<b>4.1</b>	3050	2595	2440	<b>2180</b>
								<b>59</b>	6725	5720	5380	<b>4805</b>		
								<b>4.8</b>	3400	2890	2720	<b>2430</b>		
								<b>69</b>	7495	6370	6000	<b>5360</b>		
								<b>5.4</b>	3605	3065	2885	<b>2575</b>		
								<b>78</b>	7950	6760	6360	<b>5680</b>		
								<b>6.1</b>	3815	3245	3050	<b>2725</b>		
								<b>88</b>	8410	7155	6725	<b>6010</b>		