



IM 126

For customers who are looking for a value tyre for their towed agricultural implements such as small trailers, seeders, cultivators, balers etc, the IM 126 provides good performance at value price. Its ribbed treads provide good directional stability.




TRA Code



Speed Index



Square Baler



Bale Trailer



Round Baler

Tyre Size	Rim Width (inch)	Unloaded Dimensions ±				PR	Load index / Speed symbol	TYPE	Recommended Max Load (kg/lbs)					
		SW	OD	SLR	RC				Inf. Pr	Free rolling Wheel / Speed				
		mm	mm	mm	mm					bar	10 kmph	25 kmph	30 kmph	40 kmph
		in	in	in	in					p.s.i	6 mph	15 mph	19 mph	25 mph
400/60-15.5	AG13.00	402	858	387	2608	10	136 A8	TL	2.5	3135	2665	2510	2240	
										36	6915	5875	5535	4940
										3.5	4060	3450	3250	2900
		15.8	33.8	15.2	102.7	16	147 A8	TL	4.0	4305	3660	3445	3075	
										58	9495	8070	7595	6780
										4.5	4550	3870	3640	3250
				22	153 A8	TL	5.5	5110	4345	4090	3650			
							80	11270	9580	9020	8050			
15.0/55-17	13	392	840	373	2461	14	141 A8	TL	3.7	3605	3065	2885	2575	
		15.4	33.1	14.7	96.9				54	7950	6760	6360	5680	
500/50-17	16	515	950	416	2750	14	149 A8	TL	2.8	4550	3870	3640	3250	
									41	10035	8535	8025	7165	
		20.3	37.4	16.4	108.3	18	154 A8	TL	3.6	5250	4465	4200	3750	
									52	11575	9845	9260	8270	