



IM 162

The IM 162 is designed for use in implements used for heavy duty agriculture. The thick solid lugs provide superior traction preventing slippages. The deep and ideally spaced lugs promote superior self-cleaning. It's a tyre that can used both on soft and hard underfoot conditions.



TRA Code



Speed Index



Trailer

Tyre Size	Pattern	Rim Width (inch)	Unloaded				PR	Load index / Speed symbol	TYPE	Inf. Pr bar	Recommended Max Load (kg/lbs)									
			SW	OD	SLR	RC					Free rolling Wheel					Drive Wheel				
			mm	mm	mm	mm					10 kmph/ 6mph	20 kmph/ 12mph	25 kmph/ 15mph	30 kmph/ 19mph	40 kmph/ 25mph	10 kmph/ 6mph	20 kmph/ 12mph	25 kmph/ 15mph	30 kmph/ 19mph	40 kmph/ 25mph
320/60-12	IM162	10.50 I	333	676	309	2040	-	113A8 100A8	TT	2.1	1610	1450	1370	1290	1150	1120	1010	950	895	800
			13.1	26.6	12.2	80.3	-	132 A8 120A8	TT/TL	4.0	2800	2520	2380	2240	2000	1960	1765	1665	1570	1400
280/60-15.5	IM162	AG8.00	270	745	350	2240	8	115 A8 103 A8	TL	2.4	1700	1530	1445	1360	1215	1225	1105	1040	980	875
			10.6	29.3	13.8	88.2	14	128 A8 116 A8	TL	4.0	2520	2270	2140	2015	1800	1750	1575	1490	1400	1250