



IM 18

An implement tyre with multi rib tread design ideal for farming services around the year. Built with special compounds the IM 18 tyre provides long life, excellent self-cleaning properties and stability needed for agricultural implements.



TRA Code



Speed Index



Trailer



Seeder



Round Baler



Planter



Wagon

Tyre Size	Rim Width (inch)	Unloaded Dimensions ± 2%				PR	Load index / Speed symbol	TYPE	Recommended Max Load (kg/lbs)				
		SW	OD	SLR	RC				Inf. Pr	Free rolling Wheel / Speed			
		mm	mm	mm	mm					bar	10 kmph	25 kmph	30 kmph
		REC	in	in	in				in	p.s.i	6 mph	15 mph	19 mph
10.0/80-12 (255/80-12)	9	250	714	313	2081	6	110 A8	TL	2.3	1485	1260	1185	1060
									33	3275	2780	2615	2335
		8	116 A8	TL	3.1	1750	1490	1400	1250				
	9.8	28.1	12.3	81.9	10	121 A8	TL	45	3860	3285	3085	2755	
								3.9	2030	1725	1625	1450	
								57	4475	3805	3585	3195	
7.00-12 (180/9012)	4.25	200	660	295	1969	6	95 A8	TL	2.5	965	820	775	690
		7.9	26.0	11.6	77.5				36	2130	1810	1710	1520
10.0/75-15.3	9	265	758	338	2198	8	119 A8	TT/TL	3.1	1905	1620	1525	1360
									45	4200	3570	3365	3000
		10	123 A8	TT/TL	3.9	2170	1845	1735	1550				
		57	4785	4070	3825	3420							
		12	126 A8	TT/TL	4.7	2380	2025	1905	1700				
	10.5	30.0	13.4	86.9	14	130 A8	TT/TL	68	5250	4465	4200	3750	
								5.5	2660	2260	2130	1900	
								80	5865	4985	4695	4190	
								7.1	3050	2595	2440	2180	
								103	6725	5720	5380	4805	
11.5/80-15.3	9	295	845	370	2476	10	131 A8	TT/TL	3.4	2730	2320	2185	1950
									49	6020	5115	4820	4300
		12	135 A8	TT/TL	4.1	3050	2595	2440	2180				
		59	6725	5720	5380	4805							
		14	139 A8	TT/TL	4.8	3400	2890	2720	2430				
	11.7	33.4	14.6	97.9	16	141 A8	TT/TL	69	7495	6370	6000	5360	
								5.4	3605	3065	2885	2575	
								78	7950	6760	6360	5680	
								6.1	3815	3245	3050	2725	
								88	8410	7155	6725	6010	
6.00-16 (155/100-16)	4.00E	172	715	335	2138	6	95 A8	TT	2.8	965	820	775	690
		6.8	28.1	13.2	84.2				40	2130	1810	1710	1520
10.5/65-16 (265-65-16)	W9	260	775	354	2285	10	123 A8	TT	3.8	2170	1845	1735	1550
									55	4785	4070	3825	3420
	10.2	30.5	13.9	90.0	14	130 A8	TT/TL	5.3	2660	2260	2130	1900	
								77	5865	4985	4695	4190	
10.5/80-18	W9	285	890	415	2665	10	131A8	TL	3.7	2730	2320	2185	1950
									54	6020	5115	4820	4300
	11.2	35.0	16.3	104.9	14	138A8	TL	5.1	3305	2810	2645	2360	
								74	7290	6195	5830	5205	
12.5/80-18	W9	315	980	460	2910	16	148A8	TL	4.9	4410	3750	3530	3150
		12.4	38.6	18.1	114.6				71	9725	8270	7785	6945