



IM 198

The IM 198 is a high pressure implement tyre designed with robust block pattern tread and tough carcass to be used in mixer feeders. The tyre is designed to take heavy loads and perform well on a variety of surfaces such as concrete, asphalt, field, fodder / silage yards, cattle sheds etc. It provides optimum traction on dry as well as wet and slippery surfaces



TRA Code



Speed Index



Mixer Feeder Wagon



Self Propelled Mixer Feeder

Tyre Size	Rim Width	Unloaded Dimensions ±				PR	Load index / Speed symbol	TYPE	Inf. Pr	Recommended Max Load (kg)/ Speed(kmph)							
		SW	OD	SLR	RC					Free Wheel				Drive Wheel			
	mm	mm	mm	mm	10 kmph					25 kmph	30 kmph	40 kmph	10 kmph	25 kmph	30 kmph	40 kmph	
	inch	inch	inch	inch	p.s.i					6 mph	16 mph	19 mph	25 mph	6 mph	16 mph	19 mph	25 mph
305/60-14.5	10x14.5A	315	730	330	2120	20	150A8/154A8	TL	8.0	5250	4465	4200	3750	4690	3985	3750	3350
		12.4	28.7	13.0	83.5				116	11575	9845	9260	8270	10340	8785	8270	7385