



IM 72

The IM 72 is a series of low profile implement tyre built with overlapping lug type treads. They enable the machine to be operated on both wet / soft and hard soil conditions. The IM 72 is designed to minimise soil compaction and provide good load carrying capacity. It is ideal for balers, small trailers, and other towed implements.



TRA Code



Speed Index




Round Baler



Square Baler



Trailer



Planter



Seeder

Tyre Size	Pattern	Rim Width (inch)	Unloaded Dimensions				PR	Load index / Speed symbol	TYPE	Inf. Pr	Recommended Max Load (kg)/ Speed(kmph)									
			SW	OD	SLR	RC					Free rolling Wheel					Drive Wheel				
			mm	mm	mm	mm					10 kmph	20 kmph	25 kmph	30 kmph	40 kmph	10 kmph	20 kmph	25 kmph	30 kmph	40 kmph
			REC	in	in	in					in	p.s.i	6 mph	12 mph	16 mph	19 mph	25 mph	6 mph	12 mph	16 mph
400/60-15.5	IM72	AG 13.00	405	865	387	2608	14	145 A8	TL	3.5	4060	3655	3450	3250	2900	2800	2520	2380	2240	2000
								132 A8												
			15.9	34.1	15.2	102.7	18	149 A8	TL	4.5	4550	4095	3870	3640	3250	3220	2900	2735	2575	2300
								137 A8												
			22	153 A8	TL	5.5	5110	4600	4345	4090	3650	3500	3150	2975	2800	2500				
				140 A8													80	11270	10145	9580
500/50-17	IM72	16	478	925	418	2765	14	149 A8	TL	2.8	4550	4095	3870	3640	3250	3135	2820	2665	2510	2240
								136 A8												
			16	152 A8	TL	3.2	4970	4475	4225	3975	3550	3400	3060	2890	2720	2430				
				139 A8													46	10960	9865	9315
			18	154 A8	TL	3.6	5250	4725	4465	4200	3750	3605	3245	3065	2885	2575				
				141 A8													52	11575	10420	9845