



# IT30 | IT30 F

The IT 30 IND-1 / IND-3 Industrial tyre for forklifts is designed with deep treads, which have abrasion and wear-resistant compound, to provide longer working life. It is ideal for 3 shift or round the clock operations. The strong sidewall, hardened casing and specially designed rim guard provides extra protection against punctures and damages.



TRA Code



Speed Index



Forklift



Heavy Duty Forklift



Empty Container Handler

Tyre Size	Pattern	Tube	Valve	Flap	Rim Width (inch)		Unloaded Inflated Dimensions ± 2%		PR	LI / SS	Load Capacity					Inf. Pr
											Forklift Truck upto:		Other Vehicles		Side Loaders static	
											25km/h 16 mph		10km/h	25km/h	0 km/h	
					Load wheel	Steer wheel	6 mph	16 mph			0 mph					
					kg lbs	kg lbs	kg lbs	kg lbs			kg lbs					
5.00-8	IT30	5.00-8	T 45 56	5.00-8	3.00D	3.25I	150	485	8	106 A5	1235	950	1235	950	1435	8.25
											2725	2095	2725	2095	3165	120
											1415	1090	1415	1090	1645	10.00
16x6-8	IT30	16x6-8	T 45 56	16x6-8	4.33	-	155	420	18	111 A5	3120	2405	3120	2405	3625	145
											1455	1120	1455	1120	1690	10.50
											3210	2470	3210	2470	3725	152
18x7-8	IT30	18x7-8	T 45 56	18x7-8	4.33R	5.00F	175	465	16	112 A5	1535	1180	1535	1180	1780	10.50
											3385	2600	3385	2600	3925	152
											2145	1650	2145	1650	2490	10.00
6.00-9	IT30	6.00-9	T 45 56	21x9	4.00E	-	170	540	18	125 A5	4730	3640	4730	3640	5490	145
											2210	1700	2210	1700	2565	10.50
											4875	3750	4875	3750	5655	152
21x8-9	IT30	21x8-9	T 45 56	6.00-9	6.00E	7.00E	215	530	10	118 A5	1715	1320	1715	1320	1995	8.50
											3780	2910	3780	2910	4400	123
											1945	1495	1945	1495	2255	10.50
6.50-10	IT30	6.50-10	T 45 56	6.50/7.50-10	5.00F	5.50F	190	590	14	122 A5	4290	3295	4290	3295	4970	152
											2755	2120	2755	2120	3200	10.00
											6075	4675	6075	4675	7055	145
23x9-10	IT30	23x9-10	T 45 56	23x9-10	6.50 F	-	230	585	16	134 A5	2835	2180	2835	2180	3290	10.50
											6250	4805	6250	4805	7255	152
											1950	1500	1950	1500	2265	7.75
7.00-12	IT30	7.00-12	TR75A	7.00/8.25-12	5.00S	-	200	675	10	125 A5	4300	3310	4300	3310	4995	112
											2145	1650	2145	1650	2490	9.00
											4730	3640	4730	3640	5490	131
23x10.1-12	IT30	23X10.1-12/ 23.5X11-12	TR75A	23x10.1-12	8.00 G	-	260	600	14	128 A5	2340	1800	2340	1800	2720	10.00
											5160	3970	5160	3970	6000	145
											3160	2430	3160	2430	3670	9.00
23x9-10	IT30	23x9-10	T 45 56	23x9-10	6.50 F	-	230	585	18	139 A5	6970	5360	6970	5360	8090	131
											3445	2650	3445	2650	4000	10.00
											7595	5845	7595	5845	8820	145
7.00-12	IT30	7.00-12	TR75A	7.00/8.25-12	5.00S	-	200	675	20	142 A5	3550	2730	3550	2730	4120	10.50
											7830	6020	7830	6020	9085	152
											2680	2060	2680	2060	3110	8.50
23x10.1-12	IT30	23x10.1-12	TR75A	23x10.1-12	8.00 G	-	260	600	12	133 A5	5910	4540	5910	4540	6860	123
											2755	2120	2755	2120	3200	9.00
											6075	4675	6075	4675	7055	131
23x10.1-12	IT30	23x10.1-12	TR75A	23x10.1-12	8.00 G	-	260	600	14	136 A5	2910	2240	2910	2240	3380	10.00
											6415	4940	6415	4940	7455	145
											3380	2600	3380	2600	3925	9.00
23x10.1-12	IT30	23x10.1-12	TR75A	23x10.1-12	8.00 G	-	260	600	18	141 A5	7455	5735	7455	5735	8655	131
											3880	2985	3880	2985	4505	10.50
											8555	6580	8555	6580	9935	152

\*= Under Development

