



LG 18

The LG 18 with its large contact area and ideally spaced lugs make it an ideal tyre for use in driven machines such as trenchers, orchard harvesters and speciality machinery. It is suitable for lawn & garden, soil tillage and public space and maintenance. It also provides good traction in muddy conditions.



TRA Code



Speed Index



Trencher



Turf Tractor

Tyre Size	Rim Width (inch)	Unloaded Dimensions ± 2%				PR	Type	Inflation Pressure	Recommended Max Load
		SW	OD	SLR	RC				Speed 15 kmph / 9mph
		REC	mm/in	mm/in	mm/in			mm/in	bar /p.s.i
23x8.50-12	7.00 I	218	586	262	1694	6	TL	2.3	655
								33	1445
						8.6	23.2	10.4	67.0
		44	1685						
		10	TL	4.0	900				
				58	1985				
23x10.50-12	8.50 I	256	571	256	1656	6	TL	2.2	800
								32	1765
						10.1	22.6	10.1	65.5
		44	2105						
		12	TL	4.5	1600				
				65	3530				
26x12.00-12	10.50 I	305	668	285	1882	4	TL	1.4	810
								20	1785
						12.1	26.4	11.3	74.4
		44	2790						
		12	TL	4.5	1600				
				65	3530				