



TC 09 | TC 09S


The TC 09/ TC09 S are a large volume implement flotation tyres ideal for moving heavy loads. The tyre is suitable for agricultural implements and machinery and can be used for free rolling and drive wheel use. It is also suited for towed implements such as seed drills, trailers, wagons etc., and driven machines such as site dumpers and compact wheel loaders.



TRA Code



Speed Index



Trailer



Wagon

Tyre Size	Pattern	Rim Width (inch)	Unloaded Dimensions ± 2%				PR	Load index / Speed symbol	TYPE	Inf. Pr	Recommended Load (kg/lbs)/Speed(kmph)			
			SW	OD	SLR	RC					Bar	10 kmph	30 kmph	40 kmph
		REC	mm/in	mm/in	mm/in	mm/in				P.s.i	6 mph	19 mph	25 mph	31 mph
500/45-20	TC09	16.00 DC	485	945	449	2924	-	160A8/164A6	TL	6.0	6300	5000	4500	4050
			19.1	37.2	17.7	115.1				87	13890	11025	9925	8930
500/60-22.5	TC09S	16.00 DC	508	1175	519	3438	16	159A8/163A6	TL	3.2	6125	4875	4375	3940
			20	46.3	20.4	135.3				46	13505	10750	9645	8690
550/55-22.5	TC09	16.00 DC	545	1195	519	3438	16	166A8/169A6	TL	2.8	7420	5800	5300	4770
			21.5	47	20.4	135.3				41	16360	12790	11685	10520
600/40-22.5	TC09	20.00 DC	600	1120	484	3197	-	169A8/173A6	TL	6	8120	6500	5800	5220
			23.6	44.1	19.1	125.9				87	17905	14335	12790	11510